## Accepted Manuscript

Gas cleaning with molten tin for hydrogen sulfide and tar in producer gas generated from biomass gasification

Jihong Moon, Woojin Jo, Soohwa Jeong, Byungryeul Bang, Youngtai Choi, Jungho Hwang, Uendo Lee

PII: S0360-5442(17)30687-4

DOI: 10.1016/j.energy.2017.04.121

Reference: EGY 10762

To appear in: *Energy* 

Received Date: 30 November 2016

Revised Date: 27 March 2017

Accepted Date: 22 April 2017

Please cite this article as: Moon J, Jo W, Jeong S, Bang B, Choi Y, Hwang J, Lee U, Gas cleaning with molten tin for hydrogen sulfide and tar in producer gas generated from biomass gasification, *Energy* (2017), doi: 10.1016/j.energy.2017.04.121.

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



## Gas cleaning with molten tin for hydrogen sulfide and tar in producer gas generated from biomass gasification

Jihong Moon<sup>a,b</sup>, Woojin Jo<sup>c</sup>, Soohwa Jeong<sup>b,d</sup>, Byungryeul Bang<sup>b,d</sup>, Youngtai Choi<sup>c</sup>, Jungho Hwang<sup>e</sup>, Uendo Lee<sup>b,d,f,\*</sup>

<sup>a</sup>Clean Fuel Laboratory and <sup>b</sup>Future Energy Plant (FEP) Convergence Research Center, Korea Institute of Energy Research (KIER), Gajeong-ro, Yuseong-gu, Daejeon, 34129, South Korea

<sup>c</sup>Thermal & Fluid System Group, <sup>d</sup>Thermochemical Energy System Group, Korea Institute of Industrial Technology (KITECH), 89 Yangdaegiro-gil, Ipjang, Cheonan, Chungnam, 31056, South Korea

<sup>e</sup>Department of Mechanical Engineering, Yonsei University, 50, Yonsei-ro, Seodaemun, Seoul, 03722, South Korea

<sup>f</sup>Department of Green Process and System Engineering, University of Science and Technology, 89 Yangdaegiro-gil, Ipjang, Cheonan, Chungnam, 31056, South Korea

\*Corresponding author. Tel.:+82-41-589-8574, Fax: +82-41-589-8323.

*E-mail addresses*: <u>mjh@kier.re.kr</u> (J. Moon), <u>odiumjj@kitech.re.kr</u> (W. Jo), <u>pysoo80@kitech.re.kr</u> (S. Jeong), <u>brbang@kitech.re.kr</u> (B. Bang), <u>ytchoi@kitech.re.kr</u> (Y. Choi), <u>hwangjh@yonsei.ac.kr</u> (J. Hwang), <u>uendol@kitech.re.kr</u> (U. Lee)

## Abstract

Hot gas cleaning of producer gas generated from a gasification process has many advantages in terms of thermal efficiency, gas-quality improvement, compact gasDownload English Version:

## https://daneshyari.com/en/article/5475784

Download Persian Version:

https://daneshyari.com/article/5475784

Daneshyari.com