Accepted Manuscript

Effects of the preheat layer thickness on surface/submerged flame during porous media combustion of micro burner

Ayub Ahmed Janvekar, M.A. Miskam, Aizat Abas, Zainal Arifin Ahmad, T. Juntakan, M.Z. Abdullah

PII:	S0360-5442(17)30056-7
DOI:	10.1016/j.energy.2017.01.056
Reference:	EGY 10191
To appear in:	Energy
Received Date:	09 August 2016
Revised Date:	08 January 2017
Accepted Date:	10 January 2017

Please cite this article as: Ayub Ahmed Janvekar, M.A. Miskam, Aizat Abas, Zainal Arifin Ahmad, T. Juntakan, M.Z. Abdullah, Effects of the preheat layer thickness on surface/submerged flame during porous media combustion of micro burner, *Energy* (2017), doi: 10.1016/j.energy. 2017.01.056

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



ACCEPTED MANUSCRIPT

Highlights

- 1. A study to show the cut out line between surface and submerged flame region in a burner.
- 2. Studying the effect of preheat layer thickness on surface and submerge mode.
- 3. Reaction layer with foam porous media can also undergo submerge flame.
- 4. Effects of ultra-lean equivalence ratios on micro burner.

Download English Version:

https://daneshyari.com/en/article/5476241

Download Persian Version:

https://daneshyari.com/article/5476241

Daneshyari.com