Accepted Manuscript

Use of Recycled Mixed Aggregates in Floor Blocks Manufacturing

Fernando López Gayarre, Jesús Suárez González, Rubén Blanco Viñuela, Carlos López-Colina Pérez, Miguel A. Serrano López

PII:	S0959-6526(17)31928-5
DOI:	10.1016/j.jclepro.2017.08.193
Reference:	JCLP 10452
To appear in:	Journal of Cleaner Production
Received Date:	07 May 2017
Revised Date:	31 July 2017
Accepted Date:	23 August 2017

Please cite this article as: Fernando López Gayarre, Jesús Suárez González, Rubén Blanco Viñuela, Carlos López-Colina Pérez, Miguel A. Serrano López, Use of Recycled Mixed Aggregates in Floor Blocks Manufacturing, *Journal of Cleaner Production* (2017), doi: 10.1016/j.jclepro. 2017.08.193

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



Highlights

- Recycled mix aggregates from faulty bricks from precast facilities have been used
- Hollow floor blocks have been made with recycled mixed aggregates.
- For percentages of substitution up to 35% the decrease of strength is very small.
- The aggregates used produce better results than those coming from demolitions.
- Floor blocks manufactured fulfill with standards even for a 100% of replacement.

A CER MAN

Download English Version:

https://daneshyari.com/en/article/5479486

Download Persian Version:

https://daneshyari.com/article/5479486

Daneshyari.com