Author's Accepted Manuscript

Promising Cu-doped Polyvinyl Alcohol Films for Optical and Photoconductive Applications

F.M. Ali, I. Ashraf, Sh.M. Alqahtani



 PII:
 S0921-4526(17)30702-0

 DOI:
 http://dx.doi.org/10.1016/j.physb.2017.09.107

 Reference:
 PHYSB310333

To appear in: Physica B: Physics of Condensed Matter

Received date: 10 May 2017 Revised date: 19 September 2017 Accepted date: 26 September 2017

Cite this article as: F.M. Ali, I. Ashraf and Sh.M. Alqahtani, Promising Cu-doped Polyvinyl Alcohol Films for Optical and Photoconductive Applications, *Physica B: Physics of Condensed Matter*, http://dx.doi.org/10.1016/j.physb.2017.09.107

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting galley proof before it is published in its final citable form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

ACCEPTED MANUSCRIPT

Promising Cu-doped Polyvinyl Alcohol Films for Optical and

Photoconductive Applications

F. M. Ali^{*a,b**}, I. Ashraf^{*a,d*}, Sh. M. Alqahtani^{*b*}

^a Physics department, Faculty of Science, King Khalid University, P.O. Box 9004, Abha, Saudia Arabia.

^b Physics department, Faculty of Science and Arts, King Khalid University, Saudia Arabia

^c Physics department, Faculty of Science, Suez Canal University, Ismailia, Egypt.

^d Physics department, Faculty of Science, Aswan University, Aswan, Egypt.

Abstract

Pure and Cu-doped Poly Vinyl Alcohol (PVA) film samples with different concentrations of copper (5,10,15 and 20 % weight percent) were prepared by the conventional castling technique. The structural, optical and photoconductive properties of pure and doped films were studied. X-ray diffraction pattern of the investigated samples reveals the interaction between the filler and polymer which leads to decrease the crystallinity with riching amorphous phase. Optical spectrophotometric measurements showed blocking of UV range in transmission spectra of 20% wt Cu-content where the determined indirect Optical energy gap strongly decrease from 4.96 eV for pure PVA to about 2.85 eV for this sample. Film samples exhibit positive photoconduction effect where the light reduce the resistance or increases its conduction in addition to that photosensitivity strongly increase by increasing both light intensity and copper concentration in the polymer matrix.

Keywords: Polymer films, Casting technique, Optical Absorption, Energy gap, Photoconductivity.

*Corresponding author: F. M. Ali. E.mail:fayezbakeer@yahoo.com

Download English Version:

https://daneshyari.com/en/article/5491726

Download Persian Version:

https://daneshyari.com/article/5491726

Daneshyari.com