

Characterization of Pitch Prepared from Pyrolysis Fuel Oil via Electron Beam Irradiation

Hong Gun Kim^{a,c,1}, Mira Park^{b,1}, Hak-Yong Kim^b, Lee Ku Kwac^{a,d}, Hye Kyoung Shin^{a,*1}

^aInstitute of Carbon Technology, Jeonju University, 303 Cheonjam-ro, Wansan-gu, Jeonju-si, Jeollabuk-do 55069, Republic of Korea

^bDepartment of Organic Materials & Fiber Engineering, Chonbuk National University, 567 Baekje-daero, Deokjin-gu, Jeonju-si, Jeollabuk-do 561-756, Republic of Korea

^cDepartment of Mechanical & Automotive Engineering, Jeonju University, 303 Cheonjam-ro, Wansan-gu, Jeonju-si, Jeollabuk-do 55069, Republic of Korea

^dDepartment of Manufacturing Technology and Design Engineering, Jeonju University, 303 Cheonjam-ro, Wansan-gu, Jeonju-si, Jeollabuk-do 55069, Republic of Korea

* Author to whom correspondence should be addressed. *Fax:* +82 63220 3161.

E-mail address: jokwanwoo@jj.ac.kr (H.K. Shin)

Abstract:

Pitch samples were obtained from pyrolysis fuel oil by thermal treatment for 2h at 300 °C after electron beam irradiation (EBI) treatment and by thermal treatment alone for different

¹ These authors contributed equally to this work.

Download English Version:

<https://daneshyari.com/en/article/5499228>

Download Persian Version:

<https://daneshyari.com/article/5499228>

[Daneshyari.com](https://daneshyari.com)