

Available online at [www.sciencedirect.com](http://www.sciencedirect.com)

ScienceDirect

[www.elsevier.com/locate/jes](http://www.elsevier.com/locate/jes)

# Predicting vehicle fuel consumption patterns using floating vehicle data

Yiman Du<sup>1,\*</sup>, Jianping Wu<sup>1</sup>, Senyan Yang<sup>1</sup>, Liutong Zhou<sup>2</sup>

1. Department of Civil Engineering, Tsinghua University, Beijing 100084, China

2. Department of Civil Engineering, Columbia University, New York 10027, USA

## ARTICLE INFO

### Article history:

Received 11 December 2016

Accepted 9 March 2017

Available online 18 March 2017

### Keywords:

Vehicle fuel consumption

Prediction

Floating vehicle data

## ABSTRACT

The status of energy consumption and air pollution in China is serious. It is important to analyze and predict the different fuel consumption of various types of vehicles under different influence factors. In order to fully describe the relationship between fuel consumption and the impact factors, massive amounts of floating vehicle data were used. The fuel consumption pattern and congestion pattern based on large samples of historical floating vehicle data were explored, drivers' information and vehicles' parameters from different group classification were probed, and the average velocity and average fuel consumption in the temporal dimension and spatial dimension were analyzed respectively. The fuel consumption forecasting model was established by using a Back Propagation Neural Network. Part of the sample set was used to train the forecasting model and the remaining part of the sample set was used as input to the forecasting model.

© 2017 The Research Center for Eco-Environmental Sciences, Chinese Academy of Sciences.

Published by Elsevier B.V.

## Introduction

Most of the metropolitan areas of the world are suffering from traffic congestion, excessive energy consumption and traffic emissions, which have become obstacles to the development of cities. The air pollution and energy wastefulness have caused residential environment deterioration and immeasurable economic loss (Zhang, 2014). The China National Science and Technology Development Plan clearly pointed out that the status of energy consumption and air pollution in China is serious, and the development of an integrated transport system was proposed to solve the problem of energy consumption and pollution, traffic safety and traffic congestion (National Outline for Medium and Long Term S&T Development 2006–2020, 2006).

The increase in motor vehicle travel and vehicle ownership is bound to further accelerate energy consumption, so that the

problem of energy is becoming more prominent. It has been estimated that 90% of urban air pollution in fast-growing cities in developing countries can be attributed to vehicle emissions (Zhao and Yu, 2016; United Nations Environment Program, 2010). In addition, China's traffic pollution is much higher than in other developed countries such as Japan, due to high energy consumption, high emissions and high pollution. The daily traffic jam time in Beijing increased from 3.5 hr in 2011 to 5 hr in 2008. The daily commute time of residents in China's 15 major cities is 480 million hours higher than that in European countries. One billion yuan a day is lost due to the traffic issues in these cities (Niu, 2012). Even in developed countries, millions in economic losses are caused by traffic congestion. For example, the total economic losses due to traffic congestion in 439 US cities in 2010 was 115 billion US dollars, time waste of 4.8 billion hr. and fuel waste of 1.9 billion gallons (Schrank, 2011). In Tokyo, Japan, the annual

\* Corresponding author. E-mail: [ymducp@gmail.com](mailto:ymducp@gmail.com) (Yiman Du).

transportation costs have increased by 84.2 billion yen, and economic losses of up to 12 trillion yen are caused by traffic congestion (Cao, 2009).

It is apparent that effective techniques for estimating fuel consumption costs are essential in order to reduce unnecessary fuel wastage (Siami-Irdemoosa and Dindarloo, 2015). Fuel consumption is an important economic indicator. Under the premise of limited environmental capacity, the need for gradual control of fuel consumption is inevitable to protect the earth resources and improve the atmospheric environmental quality. Therefore, it is very important to analyze and predict the different fuel consumption of various types of vehicles under the influence of different factors.

Over the past decades, there have been several major categories of methods used in fuel consumption studies (Xu, 2012). One is to focus on the characteristics of the engine. Fuel consumption can be calculated based on engine data combined with the corresponding engine cycle conditions and vehicle technical parameters. The second is to use the carbon balance method to calculate the fuel consumption. The third one is building a fuel consumption forecasting model using independent variables affecting the fuel consumption, based on real vehicle tests. Accurate and reliable data for motor vehicle fuel consumption can be obtained experimentally. However, it is limited by the experimental equipment and conditions. Therefore, the forecasting model of fuel consumption is an important means for the evaluation of traffic strategies (Yan, 2012). In an urban traffic environment, there are many factors that affect the fuel consumption forecasting model, such as vehicle performance, roads, traffic conditions, vehicle age distribution, driving range, driving speed, environmental conditions, road conditions, traffic volume, speed, etc. So far, most of the research on fuel consumption has focused on the characteristics of automobiles, and the corresponding fuel saving technology is widely used in automobile design. However, other factors such as road conditions, traffic conditions and drivers' characteristics are seldom taken into consideration. Therefore, the study of fuel consumption under consideration of different factors is of practical significance (Gao, 2007). De Vlieger (1997) found that fuel consumption will increase by 12%–40% with aggressive driving. Rakha and Ding quantified the impact of the number of stops and driving speed on fuel consumption using the VT-Micro model to prove the relationship between vehicle fuel consumption and driving behavior (Rakha and Ding, 2003).

Influenced by various factors, fuel consumption changes over a large range with no regularity. It is difficult to predict fuel consumption by using a mathematical formula. Artificial neural networks (ANNs) employ a massive interconnection of simple processing elements that incrementally learn from their environment to capture essential linear and nonlinear trends in complex data, so that they provide reliable predictions for new situations containing even noisy and partial information (Siami-Irdemoosa and Dindarloo, 2015; Schalkoff, 1997; Haykin, 1994). ANN has strong adaptability, fault tolerance and self-learning ability, and can fit arbitrarily complex nonlinear models to multidimensional data to any desired accuracy (Smith, 1996). Neural networks have been used successfully in several studies for modeling energy consumption and exhaust emissions.

In order to fully describe the relationship between fuel consumption and impact factors, a massive floating vehicle database was used in this study. The fuel consumption forecasting model was established by using a BP neural network (Back Propagation Neural Network). Part of the sample set was used to train the forecasting model and the remaining part of the sample set was used as the input to the forecasting model.

### 1. Data description

In order to fully describe the relationship between fuel consumption and the impact factors, massive samples of floating vehicle data (FVD) were collected. More than 13,000 floating vehicles in Beijing were involved in this project. The collected data included the time, location, speed, driving direction, road conditions, fuel consumption, the drivers' personal information, the vehicles' basic parameters and some other related information. Data were recorded every 30 sec from June 1 to July 31, 2012. The data amounted to about 300 GB.

Based on the FVD data, the relationship between the fuel consumption and each factor was analyzed and demonstrated in Table 1 and Figs. 1 and 2. The fuel consumption is described in terms of liters per 100 km.

$$\text{Fuel consumption of a car} = \frac{\text{Total fuel consumption of a car}}{\text{Total travel distance of this car}}$$

The independent samples t-test can be used to see if two means are different from each other when the two samples that the means are based on were taken from different individuals who have not been matched. Therefore, the independent samples t-test method was used to compare the means of two independent samples for each factor, and identify whether the statistical difference between two sample groups is probably representative of real difference. The significant difference index (Sig.) between two groups for each factor is shown in Table 1, and the Sig. values are smaller than 0.05, which denotes that the fuel consumption is statistically significantly different between the two groups for each factor.

Average fuel consumption of different urban road hierarchies and different ages is shown in Fig. 1. The average fuel consumption in arterial roads and branches is higher than the other two types of roads.

**Table 1 – The average fuel consumption in different factors.**

Fuel consumption (l/100 km)	Gender		Transmission type		Fuel type <sup>a</sup>	
	Male	Female	Auto	Manual	93#	97#
Mean	8.551	8.439	8.582	8.426	8.495	8.823
Sig.	0.01		0.01		0.03	

<sup>a</sup> The so-called No. 93, 97 unleaded petrol means that they contain respectively, 93%, 97% of the anti-knock ability of "iso-octane", which contains respectively, 7%, 3% of the anti-knock ability of pure n-heptane.

Download English Version:

<https://daneshyari.com/en/article/5754035>

Download Persian Version:

<https://daneshyari.com/article/5754035>

[Daneshyari.com](https://daneshyari.com)