



The head-on colliding process of binary liquid droplets at low velocity: High-speed photography experiments and modeling

Feng-Chao Wang, Jiang-Tao Feng, Ya-Pu Zhao*

State Key Laboratory of Nonlinear Mechanics, Institute of Mechanics, Chinese Academy of Sciences, Beijing 100190, People's Republic of China

ARTICLE INFO

Article history:

Received 15 April 2008

Accepted 1 July 2008

Available online 5 July 2008

Keywords:

Droplet collision

Rebound

Coalescence

Conglutination

Contact time

Hertz contact theory

ABSTRACT

The experimental and theoretical studies are reported in this paper for the head-on collisions of a liquid droplet with another of the same fluid resting on a solid substrate. The droplet on the hydrophobic polydimethylsiloxane (PDMS) substrate remains in a shape of an approximately spherical segment and is isometric to an incoming droplet. The colliding process of the binary droplets was recorded with high-speed photography. Head-on collisions saw four different types of response in our experiments: complete rebound, coalescence, partial rebound with conglutination, and coalescence accompanied by conglutination. For a complete rebound, both droplets exhibited remarkable elasticity and the contact time of the two colliding droplets was found to be in the range of 10–20 ms. With both droplets approximately considered as elastic bodies, Hertz contact theory was introduced to estimate the contact time for the complete rebound case. The estimated result was found to be on the same order of magnitude as the experimental data, which indicates that the present model is reasonable.

© 2008 Elsevier Inc. All rights reserved.

1. Introduction

Considerable attention has been focused on droplet collision dynamics over a very wide time span due to its fundamental importance and industrial applications. Pioneering work in droplet collisions dates back to 1879, when Lord Rayleigh noted that small droplets can rebound in collisions with a large pool of water [1,2], and it was pointed out that the failure to achieve coalescence in such circumstances is due to a layer of air trapped between the two colliding surfaces to prevent a true contact. As is well known, droplet collision and coagulation in clouds are helpful for the formation of precipitation of rainfalls. Since the presence of feeble electric forces can enhance the coalescence and formation of larger drops during such collisions, electrical charges in clouds aid in the coalescence of droplets and thus may initiate a rainfall.

Droplet impingement plays an important role in many industrial applications, including ink-jet printing, spray painting and coating, rapid spray cooling of hot surfaces. Recently, raindrops have been used to harvest electric energy for microelectromechanical systems (MEMS) from a piezoelectric system [3]. More recently, the application of droplets has been expanded to the field of biotechnology [4], such as to refill the evaporating droplets and to inject nutrients or biochemical molecules contained in a droplet into another one containing the cells. Comprehensive reviews on

the droplet collision dynamics can be found in [5,6]. The collision of a single droplet on a solid surface was studied to understand a fundamental mechanism of the complex problem [7]. Experiments show that when a droplet impacts on a solid surface, it may splash, spread, rebound, partially rebound and so on, due to different wetting properties of the surface and various impact velocities [8]. On a super-hydrophobic surface, the droplet can fully rebound with remarkable elasticity [9–11]. The contact time of a bouncing droplet with different parameters was discussed [12,13].

The collisions of free droplets were investigated as another situation [14]. The Weber number, $We = \rho v^2 R / \gamma$, and the impact parameter, $B = \chi / R$, are the key parameters that determine the behavior of collision of two liquid droplets, where ρ is the liquid density, v is the relative velocity, R is the droplet radius, γ is the surface tension, and χ is the projection of the separation distance between the droplet centers in the direction normal to that of v . Many available experiments suggest that the collision behavior of hydrocarbon drops may differ significantly from that of water drops. Qian and Law [14] obtained a regime map with respect to the Weber number and the impact parameter. Three regimes were observed in the collisions of water droplets: coalescence, off-center separation, and near head-on separation. A single droplet impact on films of the same liquid was also studied. The impact can induce coalescence, splashing, bouncing, and droplet floating on the liquid surface [15–17]. Experiments of droplets colliding onto a liquid layer supported by a solid surface show that bouncing, partial absorption, and total absorption may occur with different Weber numbers [18].

* Corresponding author. Fax: +86 10 6256 1284.

E-mail address: yzhao@imech.ac.cn (Y.-P. Zhao).

Polydimethylsiloxane (PDMS) elastomer has been widely used as a versatile material in the fabrication of microfluidic devices, rapid prototyping and nanolithography. The well-known advantages of PDMS include its optical transparency, chemical inertness and non-flammable property [19–21]. Motivated by such practical applications in microfluidics, the head-on collision of a droplet with another one resting on a horizontal PDMS substrate is studied both experimentally and theoretically in the present paper. The colliding process of the two droplets was captured with high-speed photography. Different responses after collision were observed in our experiments. Hertz contact theory was applied in a colliding model and the contact time was estimated for the complete rebound case. The influence of the various impact velocities was also discussed.

2. Materials and methods

2.1. PDMS substrate preparation

Two kinds of solid substrates were adopted in our experiments: PDMS membrane (Sylgard 184, Dow Corning, USA; ratio of the base to curing agent = 10:1) of 1.82 mm in thickness, vacuumed for an hour to remove the trapped air-bubbles; and PDMS films fabricated directly on the indium-tin-oxide (ITO) glass plate of 40 mm × 40 mm × 1.1 mm, cleaned thoroughly by the sonic cleaning method. PDMS films were spread onto the ITO glass with spin coating by spin coater (KW-4A). The relationship between the spin speed and thickness of the PDMS film was obtained in our previous research [22]. The thickness of the PDMS film was 7.6 μm, as measured with the Surface Profiler (Dektak II A).

2.2. Experimental details

In our experiment, the droplet was placed on the solid substrate and remained as a drop with a definite contact angle θ between the liquid and solid phases, which was measured with the OCA20 system (precision $\pm 0.1^\circ$) from Dataphysics, Germany, using a sessile drop method. Droplets were dropped to the substrate with a dispense unit containing a syringe needle of the system. When droplet 1 was deposited to the substrate, it kept vibrating for a while before reaching a steady state, and then droplet 2 was dropped and collided with droplet 1 (Fig. 1). The distance between the needle and the solid substrate was denoted by H . In the collision experiments, H varied from 3.8 mm to 18.2 mm, the maximum range obtainable in our experiment. Two kinds of droplets (pure water and soapy water with concentration of 2‰) were tested. The contact angle, which was denoted by θ in Fig. 1, was recorded before each collision. For the pure water droplet, the contact angle is $101.7 \pm 2.1^\circ$; for the soapy water droplet, $67.3 \pm 1.4^\circ$. The entire colliding process was recorded with high-speed photography of 400 FPS (frame per second), under the temperature of 23.0 °C and the relative humidity of 31.0%.

3. Results

Four different types of response after collisions were observed:

- (i) Complete rebound: Droplet 2 rebounded completely like an elastic ball.
- (ii) Coalescence: The two droplets coalesced directly without rebound, permanently merging into one drop.
- (iii) Partial rebound with conglutination: Conglutination occurred when droplet 2 rebounded and the two droplets separated successfully.
- (iv) Coalescence accompanied by conglutination: Droplet 2 rebounded and then coalesced with droplet 1 due to the conglutination.




Fig. 1. Schematic diagram of the collision of two droplets.

The governing parameters for the head-on collision of droplets include: the impact velocity v , the droplet radius R , the droplet density ρ , the gravitational acceleration g , the contact angle of droplet 1 with the substrate θ , the surface tension γ and the coefficient of kinetic viscosity μ of the droplets, therefore, for a type of the collision, we will have:

$$f(v, \rho, R, \mu, \gamma, g, \theta) = 0. \quad (1)$$

For the collision of unequal sized drops the ratio of the sizes becomes an important parameter, and for off-center collisions an impact angle must also be considered [23]. In the present paper, we only consider the head-on collision of two isometric droplets of the same fluid.

It is known from Buckingham's Π theorem that there are four independent dimensionless parameters: the Weber number, the Capillary number, the Bond number and the contact angle of droplet 1 with the substrate,

$$f_1(We, Ca, Bo, \theta) = 0. \quad (2)$$

The Weber number, $We = \rho v^2 R / \gamma$, represents the ratio of the inertial force to the surface tension force; the Capillary number, $Ca = \mu v / \gamma$, compares the viscosity force and the surface tension force; the Bond number, $Bo = \rho g R^2 / \gamma$, is used to for the effect of gravity of the droplet and is the ratio between the gravity force and the surface tension force. A critical scale of the droplet, namely the capillary length, can be reached when $Bo = 1$. The gravity is neglected in this study because the droplet diameter (taking droplet 2 for instance, the diameter is about 1.3 mm for pure water and 1.1 mm for soapy water) is much smaller than the capillary length (2.7 mm for pure water and 2.0 mm for soapy water). For a certain droplet, the Bond number and the contact angle are essentially fixed; hence the Weber number and the Capillary number are the most important dimensionless parameters, which play a governing role in the response of the collision.

It should be noted that there are some other dimensionless parameters for the wetting behavior, namely, the Ohnesorge number $On = \mu / \sqrt{\rho R \gamma}$, the Reynolds number $Re = \rho v R / \mu$ and the Froude number $Fr = v / \sqrt{g l}$. But, they are not independent. For example, the relation among the Capillary number, the Weber number and the Ohnesorge number can be established as: $On = Ca / \sqrt{We}$; and we also have: $Re = \sqrt{We / On}$ and $Fr = \sqrt{We / Bo}$.

Complete rebounds were observed when a pure water droplet collided with another one resting on the PDMS film coated on ITO glass. The video sequence of this process is displayed in Fig. 2. The impact velocity of droplet 2 was about 0.283 m/s, and $We = 1.47$. In this case, both droplets exhibited remarkable elasticity. A theoretical model will be developed to estimate the contact time in the next section of this paper.

Coalescences (Fig. 3) occurred much more frequently than rebounds. A capillary wave might be generated because of the unbalanced surface tension force. A new droplet might be formed

Download English Version:

<https://daneshyari.com/en/article/610891>

Download Persian Version:

<https://daneshyari.com/article/610891>

[Daneshyari.com](https://daneshyari.com)