



Decision support tool for the evaluation of landscapes



Vilém Pechanec, Jan Brus, Helena Kilianová, Ivo Machar

Palacký University, Department of Geoinformatics, 17. listopadu 50, 77146 Olomouc, Czech Republic

ARTICLE INFO

Article history:

Received 18 December 2014
Received in revised form 12 June 2015
Accepted 18 June 2015
Available online 26 June 2015

Keywords:

GIS
EMDS
Spatial decision support
Landscape ecology
Landscape valuation

ABSTRACT

This paper presents a full SDSS for landscape – its design, algorithmization and practical implementation. The created system allows simultaneous analysis and evaluation of landscape from the perspective of ecological stability, erosion susceptibility, retention capacity and the economic value. The presented system implements products ArcView GIS 3.x, EMDS 2.0 and NetWeaver 1.1. The system implements four methods which are generally accepted for the given analyses and which have been algorithmized and applied in the GIS environment many times. Ecological stability is assessed using the basic coefficients of ecological stability. The susceptibility of soil to water erosion is determined by the RUSLE method. Retention capacity is determined based on the Runoff Curve Number Method and the economic value of the landscape draws on the modified Hessen method. The result includes a filled knowledge base, an algorithmized decision-making scheme for the landscape segment assessment and an optimized data model. The practical solution is applied to the model area of the Trkmanka catchment area.

© 2015 Elsevier B.V. All rights reserved.

1. Introduction

Land management decisions are becoming increasingly important nowadays. Growing populations and consumerism are putting pressure on natural resources and biodiversity. Moreover, public awareness of land management and sustainability issues is growing in many sectors, including spatial planning, and is placing greater expectations on managers to balance competing values. Consequently, the responsibilities involved in land management are becoming more complex. The theory on decision deals with the problem of the manner of arriving at an optimized decision based on existing alternatives (Seip and Wenstøp, 2007). Usually, there is no simple guide to deriving a solution, and every decision entails a certain amount of risk. In the present-day situation of increasing anthropogenic pressure on the environment, one of the important themes is the problem of resource allocation. However, a qualified decision concerning resources requires seeking, assembling and verifying reliable information. At many decision-making levels, such information is hardly obtainable as it is difficult to combine often conflicting opinions (Prato, 1999). Today, the land represents as a very limited resource; it is, therefore, important to recognize its potential and optimize its usage (Malczewski, 2006). Due to the complexity of the requirements and the large number of criteria (environmental, economic, sociological, and natural), it is necessary to use multi-object planning techniques and multi-criteria analysis (Chakhar and Martel, 2003; Feick and Hall, 2004; Yalcin and Akyurek, 2004). The rapid process of urbanization brings along the need for effective spatial planning with

emphasis on the construction of urban infrastructure for housing, work and various supportive activities of the population (Laaribi et al., 1996). Pursuant to the high number of specific criteria (geotechnical, environmental, constructional, municipal, etc.) that must be concentrated into this planning, the application of multi-criteria analysis method may have significant impacts on the planning quality, speed and cost (McKinney and Cai, 2002; Sugumaran and DeGroot, 2011). An effective approach using the instruments of geospatial analysis methods (GIS) and multi-criteria system analyses will allow spatial planning to solve the problems associated with landscape planning in somewhat easier and faster ways (Pechanec et al., 2011). Related topics – where the instruments of decision-making systems are also applied – include the identification of plots with natural and technological prerequisites for development (Malczewski, 2006). Creating an optimal model for land assessment, which indicates the cost operation of investments and compliance with the provisions and objectives of urban development in accordance with international conventions is further demanded (Pechanec and Brus, 2012). Decision-making strategies may also become useful in evaluating other natural phenomena, such as floods, landslides, hurricanes, volcanic activity, etc. (Ponjavic and Ferhatbegović, 2010).

2. Material and methods

2.1. Definition of SDSS

Nowadays spatial planning processes increase in importance and complexity. Moreover stakeholders require more transparency in decision processes. These are often complex problems with large datasets, a high degree of uncertainty (Báčová et al., 2013; Brus et al., 2013), and

E-mail addresses: vilem.pechanec@upol.cz (V. Pechanec), jan.brus@upol.cz (J. Brus), helena.kilianova@upol.cz (H. Kilianová).

multiple stakeholders with conflicting interests and viewpoints. From this reason there is a need to formalize and rationalize decisions with available scientific information (Bonczek et al., 2014). Decision support systems (DSS) are interactive computer-based systems designed to support decision-making activities. DSS uses knowledge and theory from diverse areas such as database research, artificial intelligence, decision theory, economics, cognitive science, management science, mathematical modeling, and others. Spatial Decision Support Systems (SDSS) represent a special type of information systems. According to Sugumaran and DeGroot (2011) SDSS provide a spatial extension of Decision Support Systems (DSS), or rather an integration of GIS and DSS. SDSS are therefore usually regarded as a computer-based information system designed to assist in decision-making while solving problems which are difficult to formulate and structure, and in cases when a fully automated system cannot be applied. SDSS are closely related to knowledge-based and expert systems. A typical SDSS contains three generic components: a database management system and geographical database, a model-based management system and model base, and a dialogue generation system (Malczewski and Rinner, 2015). Chen et al. (2010) note that these systems have to be applied to complex spatial problems which are difficult to structure or can only be partly structured, rendering the decision-maker unable to define a problem or set objectives fully.

SDSS as a spatial extension of DSS have further four characteristic features:

- provide a mechanisms for spatial data input,
- enable representation of spatial relations and structures,
- encompass analytical tools for spatial and geographical analyses,
- allow the creation of spatial outputs, including maps (Sugumaran and DeGroot, 2011).

2.2. Software and data

The presented system implements products ArcView GIS 3.x, EMDS 2.0 and NetWeaver 1.1.

Ecosystem Management Decision Support (EMDS) integrates logical formalism justified on the basis of knowledge base in the GIS environment so that it provides support for decisions on evaluation and assessment of landscape from ecological point of view. The EMDS decision-making pattern is based on a knowledge base that uses fuzzy logic, network architecture and object-based approach (Reynolds, 1999). When it is interconnected with ArcGIS we get a full SDSS product (Prato, 1999). An older version of EMDS 2.0 was used to enable full application of raster data together with a compatible GIS product by Esri–ArcView GIS 3x.

NetWeaver development system that is designated for creation of knowledge base. NetWeaver knowledge bases use an object-based approach, which makes them very modular, therefore, they are easily created and maintained. NetWeaver enabled the design and creation of the evaluation network and the assessment module of EMDS then analyzed the individual landscape segments (Reynolds, 1999). All data are in shapefile format. Contour lines and streams are lines and the rest are polygons. To value landscape segments in the SDSS, the first stage requires input data processing to retrieve other characteristics which enter to the valuation network. The extent of input data needs to be adjusted relative to the extent of analyzed area, and based on the conversion tables of individual methods and corresponding mathematical relations the required attributes must be added to the input data. Data pre-processing can be performed in any GIS.

2.3. Study area

The study area for testing of SDSS tool is represented by the catchment area of the Trkmanka stream, a left-bank tributary of the Dyje River. The area is situated in South Moravia of the Czech Republic. The

catchment area covers approximately 380 km². The elongated area stretches from the north-east to south-west. Detailed description of study area can be found in Pechanec and Kilianová (2011).

2.4. Implemented methods of landscape condition analysis

The created systems allow the simultaneous analysis and evaluation of landscape from the perspective of ecological stability, erosion susceptibility, retention capacity and the economic value of the landscape. The system implements four methods which are generally accepted for the given analyses and which have been algorithmized and applied in the GIS environment. These factors were chosen based on expert decisions, availability of data sources and verification of results by field surveys. Combining these methods to one spatial decision system brings new synthesized results. Ecological stability is assessed using the basic coefficients of ecological stability, the susceptibility of soil to water erosion is determined by the RUSLE method, retention capacity is determined based on the Runoff Curve Number Method and the economic value of the landscape draws on the modified Hessen method.

The *coefficient of ecological stability* based on proportional representation of individual forms of land use can be calculated in several ways and according to different authors. The coefficient of ecological stability thus described provides information on the stability/instability of territorial units (Machar, 2012). The calculation of ecological stability in GIS is described e.g. Romportl et al. (2013).

Water erosion is manifestation of the destructive impact of water and wind on the soil surface. To determine the water erosion susceptibility of farmland and assess the efficiency of the proposed erosion control measures, the Universal Soil Loss Equation by Wischmeier and Smith (1978) is used. An extended method of erosion modeling is called RUSLE – Revised Universal Soil Loss Equation. The equation determines the susceptibility of farmland to water erosion. The calculated value represents the amount of soil which might be removed from the plot in sheet erosion, yet it does not take into account soil deposition on the plot itself or areas lying below it. The value of soil loss tolerance helps to determine the level of erosion susceptibility of a given plot and is defined as the maximum amount of soil erosion at which sufficient soil fertility may be indefinitely and economically sustained (Fernandez et al., 2003).

Water retention capacity of a landscape is ability of landscape to hold water and thus reduce the surface runoff from the area. To calculate the runoff loss from a catchment, the Runoff Curve Number (CN) method is applied. It is designed to determine the direct runoff volume and peak discharge from a proposed excess rainfall of selected frequency in unobserved profiles, particularly in catchments or their parts which are subject to farming. It is a simple model with relatively accessible inputs, it is sufficiently accurate and applicable for determining the direct runoff. Determination of water retention capacity of the landscape in GIS using the CN method is described, e.g. Chow et al. (1998), Maidment and Djokic (2000). The calculation itself is based on the assumption that the ratio of runoff to rainfall equals the ratio of the actual water retention during runoff to the potential maximum retention.

Economic assessment of the landscape draws on a modified Hessen biotope assessment method adjusted to the conditions of the Czech Republic (Seják and Dejmál, 2003). For SDSS purposes, the data processing as well as the assessment itself takes place in a GIS environment and is based on implementing a method which enables partial automation, simplification and acceleration of landscape assessment procedures in the GIS environment. Its key characteristic is a two-level assessment which encompasses an expert relative assessment of the environmental characteristics of given types of landscape (in points) and assigning specific financial sums to individual points. The method assesses biotope types according to standard typology used in the Czech Republic. The assessment of biotope type is followed by individual assessment of specific biotopes. Corrections of point values use a coefficient determined on the basis of six auxiliary criteria (Cudlín et al., 2005).

Download English Version:

<https://daneshyari.com/en/article/6295755>

Download Persian Version:

<https://daneshyari.com/article/6295755>

[Daneshyari.com](https://daneshyari.com)