

## Accepted Manuscript

A Combined Monitoring Scheme with Fuzzy Logic Filter for Plant-Wide Tennessee Eastman Process fault detection

Mustapha Ammiche, Abdelmalek Kouadri, Azzeddine Bakdi

PII: S0009-2509(18)30292-6  
DOI: <https://doi.org/10.1016/j.ces.2018.05.001>  
Reference: CES 14208

To appear in: *Chemical Engineering Science*

Received Date: 29 August 2017  
Revised Date: 13 April 2018  
Accepted Date: 2 May 2018

Please cite this article as: M. Ammiche, A. Kouadri, A. Bakdi, A Combined Monitoring Scheme with Fuzzy Logic Filter for Plant-Wide Tennessee Eastman Process fault detection, *Chemical Engineering Science* (2018), doi: <https://doi.org/10.1016/j.ces.2018.05.001>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



# A Combined Monitoring Scheme with Fuzzy Logic Filter for Plant-Wide Tennessee Eastman Process fault detection

Mustapha Ammiche, Abdelmalek Kouadri, Azzeddine Bakdi

*Signals and Systems Laboratory, Institute of Electrical and Electronics Engineering, University M'Hamed Bougara of Boumerdes, Avenue of independence, 35000*

*Boumerdès, Algeria*

*ammichemustapha@hotmail.fr, ab\_kouadri@hotmail.com, bkdaznsun@gmail.com*

## **Abstract**

Principal Component Analysis (PCA) is the most common Multivariate Statistical Process Control (MSPC) method that is widely used for Fault Detection and Diagnosis (FDD). Since early abnormality detection with high accuracy is required for safe and reliable process operation, False Alarms Rate (FAR), Missed Detection Rate (MDR) and the detection time delay are the major factors that must be taken into consideration when developing any process monitoring scheme. Unfortunately, the PCA performance, with fixed limits, is weak in terms of the stated factors. In contrast, conventional Moving Window PCA (MWPCA) is an adaptive technique which updates both the PCA model and the thresholds once a new normal observation is available. Yet, MWPCA methodology still does not reduce the MDR and the detection delay. In this paper, a Modified MWPCA (MMWPCA) with Fuzzy Logic Filter (FLF) is proposed to enhance the monitoring performance of PCA. It is an adaptive approach with a fixed model that combines both aforementioned techniques. The aim of using FLF is to ensure robustness to false alarms without affecting the Fault Detection (FD)

Download English Version:

<https://daneshyari.com/en/article/6588397>

Download Persian Version:

<https://daneshyari.com/article/6588397>

[Daneshyari.com](https://daneshyari.com)