

# Accepted Manuscript

Optimization of design flow rates and component sizing for residential ventilation

J. Laverge, A. Janssens



PII: S0360-1323(13)00099-1

DOI: [10.1016/j.buildenv.2013.03.019](https://doi.org/10.1016/j.buildenv.2013.03.019)

Reference: BAE 3380

To appear in: *Building and Environment*

Received Date: 27 November 2012

Revised Date: 27 March 2013

Accepted Date: 29 March 2013

Please cite this article as: Laverge J, Janssens A, Optimization of design flow rates and component sizing for residential ventilation, *Building and Environment* (2013), doi: 10.1016/j.buildenv.2013.03.019.

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

- exhaust and mechanical ventilation better than natural ventilation for 'wet' spaces
- improved air tightness improves ventilation system performance
- slightly higher supply flow rates improve mechanical ventilation performance
- large transfer devices improve natural and exhaust ventilation performance

ACCEPTED MANUSCRIPT

Download English Version:

<https://daneshyari.com/en/article/6700971>

Download Persian Version:

<https://daneshyari.com/article/6700971>

[Daneshyari.com](https://daneshyari.com)