Accepted Manuscript

Performance Evaluation of a High-Influx, Bubble dehumidifier

K. Sai Kiran, Benny Raphael

 PII:
 S0378-7788(17)34128-2

 DOI:
 10.1016/j.enbuild.2018.05.047

 Reference:
 ENB 8588

To appear in: Energy & Buildings

Received date:20 December 2017Revised date:13 April 2018Accepted date:26 May 2018



Please cite this article as: K. Sai Kiran, Benny Raphael, Performance Evaluation of a High-Influx, Bubble dehumidifier, *Energy & Buildings* (2018), doi: 10.1016/j.enbuild.2018.05.047

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

Highlights:

- prototype of a bubble dehumidifier that accommodates high-influx rates
- maximum moisture removal rate of 0.28 g/s resulting in 66% dehumidifier effectiveness
- semi-analytical procedure to predict performance
- developed empirical formula validated using new data root mean square error less than 10%

.

Download English Version:

https://daneshyari.com/en/article/6727469

Download Persian Version:

https://daneshyari.com/article/6727469

Daneshyari.com