

Accepted Manuscript

Title: Demand Controlled Ventilation Indoor Climate and Energy Performance in a High Performance Building with Air flow Rate Controlled Chilled Beams

Author: Kaiser Ahmed Jarek Kurnitski Pii Sormunen



PII: S0378-7788(15)30292-9
DOI: <http://dx.doi.org/doi:10.1016/j.enbuild.2015.09.052>
Reference: ENB 6172

To appear in: *ENB*

Received date: 29-6-2015
Revised date: 25-8-2015
Accepted date: 20-9-2015

Please cite this article as: K. Ahmed, J. Kurnitski, P. Sormunen, Demand Controlled Ventilation Indoor Climate and Energy Performance in a High Performance Building with Air flow Rate Controlled Chilled Beams, *Energy and Buildings* (2015), <http://dx.doi.org/10.1016/j.enbuild.2015.09.052>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

Demand Controlled Ventilation Indoor Climate and Energy Performance in a High Performance Building with Air flow Rate Controlled Chilled Beams

Kaiser Ahmed ^{1,*}, Jarek Kurnitski ^{1,3}, Piia Sormunen ²

¹ Aalto University, Department of Civil and Structural Engineering, Finland

² Helsinki Metropolia University of Applied Sciences, Department of Civil Engineering and Building Services, Finland

³ Tallinn University of Technology, Faculty of Civil Engineering, Estonia

*Corresponding author: Rakentajanaukio 4 A, FI-02150 Espoo, Finland;

E-mail: kaiser.ahmed@aalto.fi

Abstract

Indoor climate and energy performance of Finnish low energy office building were studied to determine optimal control and operation solutions of demand controlled room conditioning and ventilation system with airflow rate controlled active chilled beams. Onsite measured temperature, CO₂, occupancy rate were used to calibrate a dynamic simulations model. The results showed an average occupancy rate of 0.55 during office hours (OH) offering a good energy saving potential for Demand Control Ventilation (DCV) system. DCV system used 7 to 8% less total primary energy compared to Constant Air Volume (CAV) system depending on control and operation strategy used. DCV system saving was 33 to 41% if only heating, cooling, fans and pumps primary energy were considered. Supply air temperature controlled according to extract air temperature instead of outdoor air temperature minimized overheating problem which occurred with design solution during both seasons and systems. DCV system with active chilled beam complied at least 94% and

Download English Version:

<https://daneshyari.com/en/article/6730894>

Download Persian Version:

<https://daneshyari.com/article/6730894>

[Daneshyari.com](https://daneshyari.com)