

## Accepted Manuscript

Title: Improvement of humidification–dehumidification desalination unit using a desiccant wheel

Authors: S.A. El-Agouz, Ravishankar Sathyamurthy, A. Muthu Manokar



PII: S0263-8762(17)30323-4  
DOI: <http://dx.doi.org/doi:10.1016/j.cherd.2017.06.004>  
Reference: CHERD 2706

To appear in:

Received date: 3-4-2017  
Revised date: 5-6-2017  
Accepted date: 7-6-2017

Please cite this article as: S.A., El-Agouz, Sathyamurthy, Ravishankar, A., Muthu Manokar, Improvement of humidification–dehumidification desalination unit using a desiccant wheel. *Chemical Engineering Research and Design* <http://dx.doi.org/10.1016/j.cherd.2017.06.004>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

# Improvement of humidification–dehumidification desalination unit using a desiccant wheel

S. A. El-Agouz<sup>a,\*</sup>, Ravishankar Sathyamurthy<sup>b,c\*</sup>, A. Muthu Manokar<sup>d</sup>

<sup>a</sup>*Mechanical Power Engineering Department, Faculty of Engineering, Tanta University, Tanta, Egypt*

<sup>b</sup>*Center for Excellence in Energy and Nano Technology, S.A. Engineering College, Chennai, Tamil Nadu, India*

<sup>c</sup>*Department of Mechanical Engineering, S.A. Engineering College, Chennai, Tamil Nadu, India*

<sup>d</sup>*Department of Mechanical Engineering, Kamaraj Engineering College, Virudhunagar, Tamil Nadu, India*

\*Corresponding Authors

Dr. S.A. El-Agouz, Professor, Mechanical Power Engineering Department, Faculty of Engineering, Tanta University, Tanta, Egypt, elagouz2011@yahoo.com

Dr. Ravishankar Sathyamurthy, Professor, Center for Excellence in Energy and Nano Technology and Department of Mechanical Engineering, S.A. Engineering College, Chennai, Tamil Nadu, India, raviannauniv23@gmail.com, ravishankars@saec.ac.in

Corresponding authors: Tel.:+20506810503; +201093243110; Fax: +2040 3315861

*E-mail address:* elagouz2011@yahoo.com (S. A. El-Agouz), raviannauniv23@gmail.com (Ravishankar Sathyamurthy)

## Highlights

- HDH desalination unit using a desiccant wheel is theoretically studied.
- The optimum condition of different parameters of desalination unit is presented.
- Desalination unit with desiccant wheel is more efficient to provide distillate water.
- The maximum recovery ratio is found as 46% with minimum specific thermal energy is 0.149kWh/kg.
- The maximum total distillate rate and Gain output ratio are 0.46 kg<sub>w</sub>/kg<sub>a</sub> and 4.515.

Download English Version:

<https://daneshyari.com/en/article/7006005>

Download Persian Version:

<https://daneshyari.com/article/7006005>

[Daneshyari.com](https://daneshyari.com)