Author's Accepted Manuscript

Hydrophobic Alumina Hollow Fiber Membranes for Sucrose Concentration by Vacuum Membrane Distillation

Yi-Rui Chen, Liang-Hsun Chen, Chien-Hua Chen, Chia-Chieh Ko, Allen Huang, Chia-Ling Li, Ching-Jung Chuang, Kuo-Lun Tung



PII: S0376-7388(17)31722-2

https://doi.org/10.1016/j.memsci.2018.03.048 DOI:

MEMSCI16042 Reference:

To appear in: Journal of Membrane Science

Received date: 9 June 2017 Revised date: 8 January 2018 Accepted date: 19 March 2018

Cite this article as: Yi-Rui Chen, Liang-Hsun Chen, Chien-Hua Chen, Chia-Chieh Ko, Allen Huang, Chia-Ling Li, Ching-Jung Chuang and Kuo-Lun Tung, Hydrophobic Alumina Hollow Fiber Membranes for Sucrose Concentration by Distillation, Journal Vacuum Membrane of Membrane Science. https://doi.org/10.1016/j.memsci.2018.03.048

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting galley proof before it is published in its final citable form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

ACCEPTED MANUSCRIPT

Hydrophobic Alumina Hollow Fiber Membranes for Sucrose Concentration by Vacuum Membrane Distillation

Yi-Rui Chen^{a1}, Liang-Hsun Chen^{a1}, Chien-Hua Chen^a, Chia-Chieh Ko^a, Allen Huang^a, Chia-Ling Li^b, Ching-Jung Chuang^c, Kuo-Lun Tung^a*

^aDepartment of Chemical Engineering, National Taiwan University, Taipei 106, Taiwan ^bMaterial and Chemical Research Laboratories, Industrial Technology Research Institute, Hsinchu 310, Taiwan

^cDepartment of Chemical Engineering and R&D Center for Membrane Technology, Chung Yuan Christian University, Taoyuan 320, Taiwan

*Tel: +886-2-33663027, Fax: +886-2-23623040, E-mail: kuolun@ntu.edu.tw

Abstract

Hydrophobic alumina hollow fiber membranes were first used for sucrose concentration in a vacuum membrane distillation (VMD) system. The alumina hollow fiber membranes were prepared using the combined phase inversion and sintering method and then grafted with FAS to impart hydrophobicity. The as-prepared hydrophobic alumina hollow fiber membrane had a high mechanical strength of 191 MPa, a high water contact angle of 140° and a high liquid entry pressure of water of 5.0 bar. Fifty-two hydrophobic alumina hollow fibers were packed into a shell-and-tube module. To evaluate the sucrose concentration performance of the prepared membrane module, the effects of various parameters on the permeate flux, such as the feed flow rate, temperature, vacuum pressure and concentration, were investigated in the VMD system. In the batch sucrose concentration tests, an 8 L 10°Brix sucrose solution was successfully concentrated to 50°Brix by removing 6.4 L of

_

¹ These authors contributed equally to this work.

Download English Version:

https://daneshyari.com/en/article/7019918

Download Persian Version:

https://daneshyari.com/article/7019918

<u>Daneshyari.com</u>