

## Accepted Manuscript

Design of redundant microvascular cooling networks for blockage tolerance

Stephen J. Pety, Marcus Hwai Yik Tan, Ahmad R. Najafi, Anthony C. Gendusa,  
Philip R. Barnett, Philippe H. Geubelle, Scott R. White

PII: S1359-4311(17)32814-4  
DOI: <https://doi.org/10.1016/j.applthermaleng.2017.10.094>  
Reference: ATE 11292

To appear in: *Applied Thermal Engineering*

Received Date: 25 April 2017  
Revised Date: 14 September 2017  
Accepted Date: 18 October 2017

Please cite this article as: S.J. Pety, M.H. Yik Tan, A.R. Najafi, A.C. Gendusa, P.R. Barnett, P.H. Geubelle, S.R. White, Design of redundant microvascular cooling networks for blockage tolerance, *Applied Thermal Engineering* (2017), doi: <https://doi.org/10.1016/j.applthermaleng.2017.10.094>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



## Design of redundant microvascular cooling networks for blockage tolerance

Stephen J. Pety<sup>a,d,\*</sup>, Marcus Hwai Yik Tan<sup>b,d,\*</sup>, Ahmad R. Najafi<sup>b,d</sup>, Anthony C. Gendusa<sup>c,d</sup>,  
Philip R. Barnett<sup>c,d</sup>, Philippe H. Geubelle<sup>c,d,1</sup>, Scott R. White<sup>c,d,1</sup>

<sup>a</sup>Department of Material Science and Engineering, University of Illinois at Urbana-Champaign, 1304 W Green St.,  
Urbana, IL 61801, USA

<sup>b</sup>Department of Mechanical Science and Engineering, University of Illinois at Urbana-Champaign, 1206 W. Green  
St., Urbana, IL 61801, USA

<sup>c</sup>Department of Aerospace Engineering, University of Illinois at Urbana-Champaign, 104 S. Wright St., Urbana, IL  
61801, USA

<sup>d</sup>Beckman Institute for Advanced Science and Technology, University of Illinois at Urbana-Champaign, 405 N  
Mathews Ave., Urbana, IL 61801, USA

---

**Abstract**

Microvascular networks can provide host materials with many functions including self-healing and active cooling. However, vascular networks are susceptible to blockage which can dramatically reduce their functional performance. A novel optimization scheme is presented to design networks that provide sufficient cooling capacity even when partially blocked. Microvascular polydimethylsiloxane (PDMS) panels subject to a  $2000 \text{ W m}^{-2}$  applied heat flux and  $28.2 \text{ mL min}^{-1}$  coolant flow rate are simulated using dimensionally reduced thermal and hydraulic models and an interface-enriched generalized finite element method (IGFEM). Channel networks are optimized to minimize panel temperature while the channels are either clear (the  $O_0$  scheme), subject to the single worst-case blockage ( $O_1$ ), or subject to two worst-case blockages ( $O_2$ ). Designs are optimized with nodal degree (a measure of redundancy) ranging from 2 – 6. The results show that blockage tolerance is greatly enhanced for panels optimized while considering blockages and for panels with higher nodal degree. For example, the 6-degree  $O_1$  design only has a temperature rise of  $7 \text{ }^\circ\text{C}$  when a single channel is blocked, compared to a  $35 \text{ }^\circ\text{C}$  rise for the 2-degree  $O_0$  design. Thermography experiments on PDMS panels validate the IGFEM solver and the blockage tolerance of optimized panels.

---

\*These authors contributed equally to this work.

<sup>1</sup>Corresponding authors. Emails: swhite@illinois.edu or geubelle@illinois.edu

Download English Version:

<https://daneshyari.com/en/article/7046298>

Download Persian Version:

<https://daneshyari.com/article/7046298>

[Daneshyari.com](https://daneshyari.com)