

Accepted Manuscript

Performance Tests on Lab-scale Sensible Heat Storage Prototypes

Chilaka Ravi Chandra Rao, Hakeem Niyas, P. Muthukumar

PII: S1359-4311(17)35399-1

DOI: <https://doi.org/10.1016/j.applthermaleng.2017.10.085>


Reference: ATE 11283

To appear in: *Applied Thermal Engineering*

Received Date: 20 August 2017

Revised Date: 15 October 2017

Accepted Date: 16 October 2017



Please cite this article as: C.R.C. Rao, H. Niyas, P. Muthukumar, Performance Tests on Lab-scale Sensible Heat Storage Prototypes, *Applied Thermal Engineering* (2017), doi: <https://doi.org/10.1016/j.applthermaleng.2017.10.085>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

Performance Tests on Lab-scale Sensible Heat Storage Prototypes

Chilaka Ravi Chandra Rao¹, Hakeem Niyas², P. Muthukumar^{1*}

¹Department of Mechanical Engineering, Indian Institute of Technology Guwahati,
Guwahati 781039, Assam, India

²Department of Mechanical Engineering, National Institute of Technology Tiruchirappalli,
Tiruchirappalli 620015, Tamil Nadu, India

Abstract

This paper presents the performance tests on lab-scale sensible heat storage (SHS) prototypes made up of cast steel and concrete. Thermal storage performances of the prototypes in terms of charging/discharging times and energy storage/discharge rates have been estimated at various operating temperatures and heat transfer fluid (HTF) flow rates. These prototypes were designed in the form of a shell-and-tube type heat exchanger with a heat storage capacity of 15 MJ. Five different concrete mix designs were studied and the mix design M30 was selected for thermal storage, as they possess high compressive strength-cost ratio. Heat transfer enhancement in the concrete prototypes was incorporated by welding longitudinal fins on the HTF tubes. Hi-tech Therm 60 was used as heat transfer fluid. The charging and discharging times of cast steel (M1) prototype in the temperature range of 353-413 K were 1263 and 1803 s, respectively. The effective charging/discharging time of the concrete prototype with copper tubes (M2) and concrete prototype with MS tubes (M3) prototypes in the temperature range of 353-433 K were 5210/6297 s and 7160/7780 s, respectively. The storage performance of the system highly depends on the operating temperature range due to the temperature dependence of the thermo-physical properties of the SHS materials and the HTF.

Key words: Solar energy; sensible heat storage; performance tests; heat transfer enhancement; concrete.

* Corresponding author: Email: pmkumar@iitg.ernet.in; pmkumariitg@gmail.com
Fax: +91 361 2690762; Ph: +91 361 2582673

Download English Version:

<https://daneshyari.com/en/article/7046557>

Download Persian Version:

<https://daneshyari.com/article/7046557>

[Daneshyari.com](https://daneshyari.com)