## **Accepted Manuscript**

Air cavities at the inner cylinder of turbulent Taylor-Couette flow

Ruben A. Verschoof, Dennis Bakhuis, Pim A. Bullee, Sander G. Huisman, Chao Sun, Detlef Lohse


PII: \$0301-9322(17)30950-3

DOI: 10.1016/j.ijmultiphaseflow.2018.04.016

Reference: IJMF 2795

To appear in: International Journal of Multiphase Flow

Received date: 6 December 2017 Revised date: 22 March 2018 Accepted date: 29 April 2018



Please cite this article as: Ruben A. Verschoof, Dennis Bakhuis, Pim A. Bullee, Sander G. Huisman, Chao Sun, Detlef Lohse, Air cavities at the inner cylinder of turbulent Taylor-Couette flow, *International Journal of Multiphase Flow* (2018), doi: 10.1016/j.ijmultiphaseflow.2018.04.016

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

## HIGHLIGHTS

- Study on the effect of air cavities in Taylor-Couette flow
- Flow visualizations show dependence on Reynolds number, void fraction, and axial position
- $\bullet$  Large difference between net and gross drag reduction

• Local air injection is not crucial for efficient drag reduction -as long as sufficient air is available anywhere in the flow.



## Download English Version:

## https://daneshyari.com/en/article/7060085

Download Persian Version:

https://daneshyari.com/article/7060085

<u>Daneshyari.com</u>