

Accepted Manuscript

Title: Influence of Cavity Shape on Synthetic Jet Performance

Author: Mark A. Feero Philippe Lavoie Pierre E. Sullivan

PII: S0924-4247(14)00510-X

DOI: <http://dx.doi.org/doi:10.1016/j.sna.2014.12.004>


Reference: SNA 8986

To appear in: *Sensors and Actuators A*

Received date: 27-6-2014

Revised date: 29-11-2014

Accepted date: 6-12-2014



Please cite this article as: Mark A. Feero, Philippe Lavoie, Pierre E. Sullivan, Influence of Cavity Shape on Synthetic Jet Performance, *Sensors & Actuators: A. Physical* (2014), <http://dx.doi.org/10.1016/j.sna.2014.12.004>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

Influence of Cavity Shape on Synthetic Jet Performance

Mark A. Feero*, Philippe Lavoie[†] and Pierre E. Sullivan[‡]

University of Toronto, Toronto, Ontario, Canada

A synthetic jet is an unsteady jet that transfers linear momentum to the surroundings by alternately ingesting and expelling fluid from a cavity containing an oscillating diaphragm. This work presents the first experimental effort to validate the limited number of numerical investigations that have postulated synthetic jets are insensitive to cavity shape. Three axisymmetric synthetic jets with different cavity shapes were used to examine jet performance while keeping other parameters constant such as cavity volume, nozzle length and orifice diameter. Cylindrical, conical and contraction shaped cavities were considered. The cavity pressure and velocity at the orifice exit plane were measured using a microphone and hot-wire, respectively. The results demonstrated that for several operating conditions near Helmholtz resonance of the cavity, noticeable differences were observed in the radial velocity profiles between the three geometries. The Reynolds number decreased sequentially from the cylindrical to conical to contraction cavity. The momentum flux, which is relevant in flow control applications, followed the same trend. In general, the experimental results showed that synthetic jet performance is, to some degree, dependant on cavity shape.

Keywords: Synthetic jet, Fluidic actuator, Cavity shape

*PhD Student (corresponding author), Institute for Aerospace Studies, 4925 Dufferin Street, Toronto, Ontario, M3H 5T6, Canada, m.feero@mail.utoronto.ca, +1 (416) 667-7716

[†]Professor, Institute for Aerospace Studies, lavoie@utias.utoronto.ca

[‡]Professor, Mechanical and Industrial Engineering, sullivan@mie.utoronto.ca

Download English Version:

<https://daneshyari.com/en/article/7136209>

Download Persian Version:

<https://daneshyari.com/article/7136209>

[Daneshyari.com](https://daneshyari.com)