

Accepted Manuscript

Title: Enhanced resolution of a surface plasmon resonance sensor detecting C-reactive protein via a bimetallic waveguide-coupled mode approach

Authors: Hwa-Seub Lee, Tae-Yeon Seong, Won Mok Kim, Inho Kim, Gyu-Weon Hwang, Wook Seong Lee, Kyeong-Seok Lee



PII: S0925-4005(18)30634-8
DOI: <https://doi.org/10.1016/j.snb.2018.03.136>
Reference: SNB 24421

To appear in: *Sensors and Actuators B*

Received date: 31-10-2017
Revised date: 19-3-2018
Accepted date: 22-3-2018

Please cite this article as: Hwa-Seub Lee, Tae-Yeon Seong, Won Mok Kim, Inho Kim, Gyu-Weon Hwang, Wook Seong Lee, Kyeong-Seok Lee, Enhanced resolution of a surface plasmon resonance sensor detecting C-reactive protein via a bimetallic waveguide-coupled mode approach, *Sensors and Actuators B: Chemical* <https://doi.org/10.1016/j.snb.2018.03.136>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

Enhanced resolution of a surface plasmon resonance sensor detecting C-reactive protein via a bimetallic waveguide-coupled mode approach

Hwa-Seub Lee^{1,2}, Tae-Yeon Seong², Won Mok Kim¹, Inho Kim¹, Gyu-Weon Hwang¹, Wook Seong Lee¹, Kyeong-Seok Lee^{1,3,*}

¹*Center for Electronic Materials, Korea Institute of Science and Technology, Seoul 02792, Korea*

²*Department of Materials Science and Engineering, Korea University, Seoul 02841, Korea*

³*Department of Nanomaterials Science and Engineering, Korea University of Science and Technology, Daejeon 34113, Korea*

*Corresponding author. Tel.: +82 2 958 6734; Fax: +82 2 958 5509

E-mail address: kslee21@kist.re.kr (K.-S. Lee).

Highlights

- Enhanced resolution of Bi-WCSPR sensors for the detection of CRP is systematically demonstrated.
- SPR sensorgrams were measured at different CRP concentrations in both the intensity and angular interrogation modes.
- The sensing performance of Bi-WCSPR configurations was evaluated in terms of FOM and LOD.

Download English Version:

<https://daneshyari.com/en/article/7139806>

Download Persian Version:

<https://daneshyari.com/article/7139806>

[Daneshyari.com](https://daneshyari.com)