


FSI Simulation of Two Back-to-Back Wind Turbines in Atmospheric Boundary Layer Flow

A. Korobenko, J. Yan, S.M.I. Gohari, S. Sarkar, Y. Bazilevs

PII: S0045-7930(17)30171-8  
DOI: [10.1016/j.compfluid.2017.05.010](https://doi.org/10.1016/j.compfluid.2017.05.010)  
Reference: CAF 3480



To appear in: *Computers and Fluids*

Received date: 15 September 2016  
Revised date: 20 April 2017  
Accepted date: 12 May 2017

Please cite this article as: A. Korobenko, J. Yan, S.M.I. Gohari, S. Sarkar, Y. Bazilevs, FSI Simulation of Two Back-to-Back Wind Turbines in Atmospheric Boundary Layer Flow, *Computers and Fluids* (2017), doi: [10.1016/j.compfluid.2017.05.010](https://doi.org/10.1016/j.compfluid.2017.05.010)

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

**Highlights**

- A new formulation for ABL flow is integrated into an FSI framework
- Formulation employed in FSI of two back-to-back 5 MW wind turbines.
- A multi-domain modeling (MDM) approach is adopted for efficiency.
- Power-production deficit is predicted for the downstream turbine.
- Importance of FSI coupling in wind-turbine ABL simulations is highlighted.

Download English Version:

<https://daneshyari.com/en/article/7156600>

Download Persian Version:

<https://daneshyari.com/article/7156600>

[Daneshyari.com](https://daneshyari.com)