
Accepted Manuscript

Microplane Model with relaxed kinematic Constraint in the Framework of Micro Polar Cosserat Continuum

Joško Ožbolt, Serena Gambarelli

PII:	S0013-7944(18)30184-X
DOI:	https://doi.org/10.1016/j.engfracmech.2018.06.012
Reference:	EFM 6034
To appear in:	Engineering Fracture Mechanics
Received Date:	15 February 2018
Revised Date:	7 May 2018
Accepted Date:	11 June 2018



Please cite this article as: Ožbolt, J., Gambarelli, S., Microplane Model with relaxed kinematic Constraint in the Framework of Micro Polar Cosserat Continuum, *Engineering Fracture Mechanics* (2018), doi: https://doi.org/10.1016/j.engfracmech.2018.06.012

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

ACCEPTED MANUSCRIPT

Microplane Model with relaxed kinematic Constraint in the Framework of Micro Polar Cosserat Continuum

Joško Ožbolt¹ and Serena Gambarelli²

¹Institute of Construction Materials University of Stuttgart, 70560 Stuttgart, Germany E-mail: <u>ozbolt@iwb.uni-stuttgart.de</u>

²Institute of Construction Materials University of Stuttgart, 70560 Stuttgart, Germany E-mail: <u>serena.gambarelli@iwb.uni-stuttgart.de</u>

ABSTRACT: Modeling materials which exhibit cracking and damage phenomena in the framework of standard continuum together with standard finite elements leads to results that are mesh-dependent. In the present contribution a microplane model with relaxed kinematic constraint is formulated in the framework of higher order Micro Polar Cosserat continuum and combined with the regularization based on the energy (crack band method). Similar as for the standard continuum, the non-symmetric macroscopic strain tensor is on each microplane decomposed into volumetric, deviatoric and shear component (V-D-T split). The model is characterized by the two length scales, torsional and bending, that for dominant shear stress-strain state assure objectivity of the results with respect to the discretization. It is implemented into a 3D finite element (FE) code and first verified on a simple layer of finite elements loaded in shear. Subsequently, 3D FE analysis is carried out for typical concrete applications: simple shear, uniaxial compression, 3-point bending of pre-notched beam and the mixed-mode crack propagation performed on a single-edge-notched beam specimen. It is demonstrated that the higher order micro polar Cosserat continuum in combination with the crack band method leads to the results that are independent of the spatial discretization.

Keywords: Cosserat continuum, Concrete, Fracture, Microplane model, Finite elements

INTRODUCTION

In the framework of standard continuum mechanics a solid body is considered through idealized infinitesimal volumes. These volumes are connected through the Download English Version:

https://daneshyari.com/en/article/7168694

Download Persian Version:

https://daneshyari.com/article/7168694

Daneshyari.com