

## Accepted Manuscript

Stress Intensity Factor Solutions for Fretting Fatigue using Stress Gradient Factor

Marcelo Avelar Antunes, Cosme Roberto Moreira da Silva, Eduardo Martins Fontes do Rêgo, Antonio Carlos de Oliveira Miranda

PII: S0013-7944(17)30874-3  
DOI: <https://doi.org/10.1016/j.engfracmech.2017.10.031>  
Reference: EFM 5734

To appear in: *Engineering Fracture Mechanics*

Received Date: 21 August 2017  
Revised Date: 26 October 2017  
Accepted Date: 27 October 2017

Please cite this article as: Avelar Antunes, M., Roberto Moreira da Silva, C., Martins Fontes do Rêgo, E., Carlos de Oliveira Miranda, A., Stress Intensity Factor Solutions for Fretting Fatigue using Stress Gradient Factor, *Engineering Fracture Mechanics* (2017), doi: <https://doi.org/10.1016/j.engfracmech.2017.10.031>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



## Stress Intensity Factor Solutions for Fretting Fatigue using Stress Gradient Factor

Marcelo Avelar Antunes<sup>a</sup>, Cosme Roberto Moreira da Silva<sup>a</sup>, Eduardo Martins Fontes do Rêgo<sup>b</sup>, Antonio Carlos de Oliveira Miranda<sup>1c</sup>

<sup>a</sup>Department of Mechanical Engineering, University of Brasília, SG-9 Building, Darcy Ribeiro Campus, DF, 70.910-900, Brazil

<sup>b</sup>Department of Structure, Federal University of Piauí, Technology Center, University Campus Ministro Petrônio Portella, PI, 64049-550, Brazil

<sup>c</sup>Department of Civil and Environmental Engineering, University of Brasília, SG-12 Building, Darcy Ribeiro Campus, DF, 70.910-900, Brazil

marcelo.avelar.antunes@gmail.com, cosmeroberto@gmail.com,  
e\_eduardofontes@ufpi.edu.br, acmiranda@unb.br

### ABSTRACT

This paper presents stress intensity factor (SIF) solutions for fretting fatigue conditions by including a stress gradient factor (SGF) to correct the classic geometry factor for tension semi-infinite strip (TSIS) specimen. This gradient factor considers the stress gradient due to the pressure of the pad on the surface of the specimen, which creates a high concentration of stresses around the contact of the bodies. To obtain these solutions, 2D finite element model simulations were performed varying important fretting parameters, namely: coefficient of friction, bulk stress intensity, pad radius and material. All configurations respected a partial slip contact condition and the results obtained show agreement with the ones obtained analytically. Weight functions were used to obtain stress intensity factors under mode I, then to compute the SGF, which were fit into equations with a unique structure, varying only coefficients. To consider real problems, a 3D correction factor was introduced. The final SGF presented a general form to compute SIF under fretting conditions when applied in suggested methods, such as: Strain-based Fracture Mechanics, Theory of Critical Distances (TCD) and Stress Gradient.

**Keywords:** Fretting Fatigue, Weight Function, Stress Intensity Factor, Stress Gradient Factor.

---

<sup>1</sup> Corresponding author. Phone: +55-61-3107-0994; fax: +55-61-3273-4644. E-mail: acmiranda@unb.br

Download English Version:

<https://daneshyari.com/en/article/7169328>

Download Persian Version:

<https://daneshyari.com/article/7169328>

[Daneshyari.com](https://daneshyari.com)