

Author's Accepted Manuscript

Topology Optimisation of Adhesive Joints Using
Non-Parametric Methods

H. Ejaz, A. Mubashar, I.A. Ashcroft, Emad Uddin,
M. Khan



PII: S0143-7496(17)30196-3
DOI: <https://doi.org/10.1016/j.ijadhadh.2017.11.003>
Reference: JAAD2078

To appear in: *International Journal of Adhesion and Adhesives*

Received date: 30 July 2017
Accepted date: 21 October 2017

Cite this article as: H. Ejaz, A. Mubashar, I.A. Ashcroft, Emad Uddin and M. Khan, Topology Optimisation of Adhesive Joints Using Non-Parametric Methods, *International Journal of Adhesion and Adhesives*, <https://doi.org/10.1016/j.ijadhadh.2017.11.003>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting galley proof before it is published in its final citable form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

Topology Optimisation of Adhesive Joints Using Non-Parametric Methods

H. Ejaz^a, A. Mubashar^a, I. A. Ashcroft^{b1}, Emad Uddin^a, M. Khan^c

^a*Computational Mechanics Group, Department of Mechanical Engineering, School of Mechanical and Manufacturing Engineering, National University of Sciences and Technology (NUST), H-12, Islamabad, Pakistan*

^b*Faculty of Engineering, University of Nottingham, Nottingham, NG7 2RD, UK*

^c*Department of Manufacturing and Design Engineering, School of Mechanical and Manufacturing Engineering, National University of Sciences and Technology (NUST), H-12, Islamabad, Pakistan*

Abstract

This research investigates the applicability of non-parametric structural optimisation algorithms for the optimisation of structural adhesive joints. Three types of adhesive joint; single lap, double lap and double lap strap, were used for the structural optimisation. Evaluation of the non-parametric solver was carried out by first optimising the adherend geometry of the adhesive joints and then including the adhesive fillets in the optimisation domain. Thus, optimisation of single and then multiple material domains was performed. It was noted that most of the structural features of adhesive joints can be optimised by a non-parametric optimiser, however, a few limitations of the solver for adhesive joint applications were also discovered. Engineering judgement may be needed when extracting the optimised geometries for further use. A significant reduction in the stresses in the adhesive layer were observed after the optimisation of all three types of selected joints, indicating the potential of these techniques, however a clear understanding of both the optimization methods and the engineering design requirements and constraints is needed for their effective application for adhesive joints.

¹ Corresponding Author. Email: ian.ashcroft@nottingham.ac.uk

Download English Version:

<https://daneshyari.com/en/article/7170995>

Download Persian Version:

<https://daneshyari.com/article/7170995>

[Daneshyari.com](https://daneshyari.com)