

Accepted Manuscript

Impacts of heating and surfactant treatments on the geotechnical properties of a cohesive soil

A.R. Estabragh , M. Babalar , A.A. Javadi , E. Afsari

PII: S0020-7403(17)33408-2
DOI: [10.1016/j.ijmecsci.2017.11.047](https://doi.org/10.1016/j.ijmecsci.2017.11.047)
Reference: MS 4063



To appear in: *International Journal of Mechanical Sciences*

Received date: 14 December 2016
Revised date: 17 August 2017
Accepted date: 29 November 2017

Please cite this article as: A.R. Estabragh , M. Babalar , A.A. Javadi , E. Afsari , Impacts of heating and surfactant treatments on the geotechnical properties of a cohesive soil, *International Journal of Mechanical Sciences* (2017), doi: [10.1016/j.ijmecsci.2017.11.047](https://doi.org/10.1016/j.ijmecsci.2017.11.047)

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

Highlights

- Properties of soil contaminated with gasoline are different from natural soil and dependent on the degree of gasoline concentration.
- Both thermal and washing techniques are effective in remediation of soil contaminated with gasoline and the efficiency of it is dependent on the concentration of gasoline.
- It seems that using surfactants is more effective than heating in remediation of contaminated soil with gasoline.

ACCEPTED MANUSCRIPT

Download English Version:

<https://daneshyari.com/en/article/7173666>

Download Persian Version:

<https://daneshyari.com/article/7173666>

[Daneshyari.com](https://daneshyari.com)