

Accepted Manuscript

Fretting studies on electroplated brass contacts

Kyungmok Kim

PII: S0020-7403(17)33380-5
DOI: [10.1016/j.ijmecsci.2018.03.012](https://doi.org/10.1016/j.ijmecsci.2018.03.012)
Reference: MS 4222



To appear in: *International Journal of Mechanical Sciences*

Received date: 27 November 2017
Revised date: 2 March 2018
Accepted date: 12 March 2018

Please cite this article as: Kyungmok Kim , Fretting studies on electroplated brass contacts, *International Journal of Mechanical Sciences* (2018), doi: [10.1016/j.ijmecsci.2018.03.012](https://doi.org/10.1016/j.ijmecsci.2018.03.012)

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

Highlights

- Friction between self-mated gold coatings is lower than that between tin coatings.
- An electrical resistance during fretting evolves exponentially.
- An electrical resistance can be described with a *Kachanov*-type damage form.
- The evolution rate of the electrical resistance depends on temperature.

Download English Version:

<https://daneshyari.com/en/article/7173792>

Download Persian Version:

<https://daneshyari.com/article/7173792>

[Daneshyari.com](https://daneshyari.com)