Accepted Manuscript

Notched specimen under compression for ductile failure criteria

Petr Kubík, František Šebek, Jindřich Petruška

 PII:
 S0167-6636(18)30145-5

 DOI:
 10.1016/j.mechmat.2018.07.004

 Reference:
 MECMAT 2897

To appear in:

Mechanics of Materials

Received date:20 February 2018Revised date:30 May 2018Accepted date:6 July 2018

Please cite this article as: Petr Kubík, František Šebek, Jindřich Petruška, Notched specimen under compression for ductile failure criteria, *Mechanics of Materials* (2018), doi: 10.1016/j.mechmat.2018.07.004

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



Highlights

- Three advanced plasticity and ductile fracture models are implemented and employed.
- Novel compression specimen made from aluminium alloy 2024-T351 is presented.
- Stress state and ductile failure of notched cylinder is computationally studied.
- Drawbacks of complex yield criteria in terms of wrong predictions are discussed.

Download English Version:

https://daneshyari.com/en/article/7178476

Download Persian Version:

https://daneshyari.com/article/7178476

Daneshyari.com