

Accepted Manuscript

Optimizing availability of heterogeneous standby systems exposed to shocks

Gregory Levitin , Maxim Finkelstein , Yuanshun Dai

PII: S0951-8320(17)30736-6
DOI: [10.1016/j.res.s.2017.10.021](https://doi.org/10.1016/j.res.s.2017.10.021)
Reference: RESS 5989



To appear in: *Reliability Engineering and System Safety*

Received date: 20 June 2017
Revised date: 27 September 2017
Accepted date: 21 October 2017

Please cite this article as: Gregory Levitin , Maxim Finkelstein , Yuanshun Dai , Optimizing availability of heterogeneous standby systems exposed to shocks, *Reliability Engineering and System Safety* (2017), doi: [10.1016/j.res.s.2017.10.021](https://doi.org/10.1016/j.res.s.2017.10.021)

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

Highlights

- We considers heterogeneous 1-out-of-N warm standby systems subject to shocks
- The resilience to shocks decreases with the number of experienced shocks
- A preventive replacement policy with respect to shocks is considered
- The expression for availability of a system is derived
- Optimization problem for replacement policy is considered.

ACCEPTED MANUSCRIPT

Download English Version:

<https://daneshyari.com/en/article/7195313>

Download Persian Version:

<https://daneshyari.com/article/7195313>

[Daneshyari.com](https://daneshyari.com)