

## Accepted Manuscript

Title: Control of Residual Stress and Distortion in Aluminium Wire + Arc Additive Manufacture with Rolling

Authors: J.R. Hönnige, P.A. Colegrove, S. Ganguly, E. Eimer, S. Kabra, S. Williams



PII: S2214-8604(17)30354-8  
DOI: <https://doi.org/10.1016/j.addma.2018.06.015>  
Reference: ADDMA 429

To appear in:

Received date: 8-8-2017  
Revised date: 24-5-2018  
Accepted date: 18-6-2018

Please cite this article as: Hönnige JR, Colegrove PA, Ganguly S, Eimer E, Kabra S, Williams S, Control of Residual Stress and Distortion in Aluminium Wire + Arc Additive Manufacture with Rolling, *Additive Manufacturing* (2018), <https://doi.org/10.1016/j.addma.2018.06.015>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.


## Control of Residual Stress and Distortion in Aluminium Wire + Arc Additive Manufacture with Rolling

J. R. Hönnige, P. A. Colegrove, S. Ganguly, E. Eimer, S. Kabra\*, S. Williams

Welding Engineering and Laser Processing Centre (WELPC), Cranfield University, Cranfield, Bedfordshire, MK43 0AL, UK

\*ISIS Facility, Science and Technology Facilities Council, Rutherford Appleton Laboratory, Harwell Oxford, Didcot, Oxfordshire, OX11 0QX, UK

Graphical abstract



### Abstract

Rolling can control residual stress and distortion in aluminium Wire + Arc Additively Manufactured (WAAM) walls. It was applied both vertically to each deposited layer (inter-pass) and to the side of the wall after deposition is completed. Distortion was virtually eliminated with the vertical inter-pass method (unlike other metals) and inverted with side rolling. Neutron diffraction stress measurements show that the deposited wall contains constant tensile residual stresses along the build direction that reach the flow strength of the alloy in longitudinal direction. Vertical inter-pass rolling eliminates the distortion, but produces a multi-directional stress field, with hydrostatic compressive stresses approximately 2 mm below the top surface and hydrostatic tension 5-10 mm below the surface. Side rolling was even more effective in stress and distortion control and produced fairly uniform longitudinal compressive stresses along the wall height. An interesting by-product of the neutron diffraction measurements is the observation of a significantly larger FCC aluminium unit cell in the inter-pass rolled walls. This is a result of less copper in solid solution with the aluminium matrix, indicating greater precipitation which could have contributed to the material's improved strength.

Download English Version:

<https://daneshyari.com/en/article/7205815>

Download Persian Version:

<https://daneshyari.com/article/7205815>

[Daneshyari.com](https://daneshyari.com)