

Effects of test sample shape and surface production method on the fatigue behaviour of PMMA bone cement

E.M. Sheafi, K.E. Tanner



www.elsevier.com/locate/jmbbm

PII: S1751-6161(13)00293-2
DOI: <http://dx.doi.org/10.1016/j.jmbbm.2013.08.023>
Reference: JMBBM950

To appear in: *Journal of the Mechanical Behavior of Biomedical Materials*

Received date: 29 April 2013
Revised date: 14 August 2013
Accepted date:
19 August 2013

Cite this article as: E.M. Sheafi, K.E. Tanner, Effects of test sample shape and surface production method on the fatigue behaviour of PMMA bone cement, *Journal of the Mechanical Behavior of Biomedical Materials*, <http://dx.doi.org/10.1016/j.jmbbm.2013.08.023>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting galley proof before it is published in its final citable form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

Effects of test sample shape and surface production method on the fatigue behaviour of PMMA bone cement

E. M. Sheafi, K.E. Tanner

School of Engineering, University of Glasgow, Glasgow, G12 8QQ, UK

Corresponding Author:
Emadeddin M. Sheafi
School of Engineering,
James Watt South Building,
University of Glasgow,
Glasgow,
G12 8QQ,
UK
Phone: +44-141-330-8265
Fax: +44-141-330-4343
e.sheafi.1@research.gla.ac.uk

Download English Version:

<https://daneshyari.com/en/article/7209070>

Download Persian Version:

<https://daneshyari.com/article/7209070>

[Daneshyari.com](https://daneshyari.com)