

Accepted Manuscript

Thermoforming simulation of multilayer composites with continuous fibres and thermoplastic matrix

Peng Wang, Nahiène Hamila, Philippe Boisse

PII: S1359-8368(13)00147-9

DOI: <http://dx.doi.org/10.1016/j.compositesb.2013.03.045>

Reference: JCOMB 2327

To appear in: *Composites: Part B*

Received Date: 2 November 2012

Revised Date: 17 March 2013

Accepted Date: 26 March 2013

Please cite this article as: Wang, P., Hamila, N., Boisse, P., Thermoforming simulation of multilayer composites with continuous fibres and thermoplastic matrix, *Composites: Part B* (2013), doi: <http://dx.doi.org/10.1016/j.compositesb.2013.03.045>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



**Thermoforming simulation of multilayer composites
with continuous fibres and thermoplastic matrix**

Peng Wang^{1,2}, Nahiène Hamila¹, Philippe Boisse^{1,*}

¹ University of Lyon, INSA-Lyon, LaMCos, F-69621, France

² University of Lille, ENSAIT, GEMTEX, F-59056, France

Abstract: Continuous Fibre Reinforced Thermoplastics (CFRTP) have made their way into the aerospace and automotive industries as structural components. Thermoplastic composites offer many advantages over thermoset composites such as low cycle time and recyclability. The development of a thermoforming process is complex and expensive to achieve by trial/error. This can be favourably replaced by numerical analyses. A simulation approach for thermoforming of multilayer thermoplastic is presented. Each prepreg layer is modelled by semi-discrete shell elements. These elements consider the tension, in-plane shear and bending behaviour of the ply at different temperatures around the fusion point. The contact/friction during the forming process is taken into account using forward increment Lagrange multipliers. A lubricated friction model is implemented between the layers and for ply/tool friction. Thermal and forming simulations are presented and compared to experimental results. The computed shear angles after forming and wrinkles are in good agreement with the thermoforming experiment. It will be shown by the comparison of two simulations that the temperature field plays an important role in the process success.

Keywords: A. Prepreg; B. Thermomechanical, C. Finite element analysis; E. Forming; Thermoforming;

* Corresponding author: philippe.boisse@insa-lyon.fr;

Tel.: +33 4 72 43 63 96; fax.: +33 4 72 43 85 25

Download English Version:

<https://daneshyari.com/en/article/7213777>

Download Persian Version:

<https://daneshyari.com/article/7213777>

[Daneshyari.com](https://daneshyari.com)