

## Accepted Manuscript

Title: A simplified modal expansion formalism adapted to the optical design of resonant cavity enhanced photodetectors using metallic gratings

Author: Maximilien Billet Emilien Peytavit

PII: S0030-4026(17)31248-2  
DOI: <https://doi.org/doi:10.1016/j.ijleo.2017.10.041>  
Reference: IJLEO 59777

To appear in:

Received date: 4-7-2017  
Accepted date: 8-10-2017



Please cite this article as: Maximilien Billet, Emilien Peytavit, A simplified modal expansion formalism adapted to the optical design of resonant cavity enhanced photodetectors using metallic gratings, *Optik - International Journal for Light and Electron Optics* (2017), <https://doi.org/10.1016/j.ijleo.2017.10.041>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

# A simplified modal expansion formalism adapted to the optical design of resonant cavity enhanced photodetectors using metallic gratings

Maximilien Billet, Emilien Peytavit

*IEMN (Institute of Electronics, Microelectronics and Nanotechnology) Univ. Lille, CNRS, Centrale Lille, ISEN, Univ. Valenciennes, UMR 8520 - IEMN, F-59652 Villeneuve d'Ascq, France*

---

## Abstract

In this communication, we present a method to model the light absorption in a resonant photoconductor based on a photoconductive layer sandwiched between a metallic grating in front side and a metallic backside mirror. We started from a modal expansion formalism previously developed in order to model the transmission and the reflection of an infinite array of holes and we added the effect of a stack of homogeneous layers ended by a metallic mirror. It is finally shown that the electromagnetic response of the structure calculated with this numerical method is in good agreement with a more rigorous method such as the rigorous coupled wave analysis, whereas it requires a much lower computing power.

**Keywords:** Ultrafast Photodetector, Modal expansion analysis, Diffraction Gratings

**2010 MSC:** 00-01, 99-00

---

## 1. Introduction

Ultrafast photodetectors are key devices for the generation and the detection of THz waves based on the laser and optoelectronics technologies[1],[2]. As far as now, the devices which present suitable properties for these applications,

---

*Email address:* `emilien.peytavit@iemn.univ-lille1.fr` (Emilien Peytavit)

*Preprint submitted to Optik*

*July 4, 2017*

Download English Version:

<https://daneshyari.com/en/article/7225401>

Download Persian Version:

<https://daneshyari.com/article/7225401>

[Daneshyari.com](https://daneshyari.com)