Accepted Manuscript

High-performance noncontact thermal diode via asymmetric nanostructures

Jiadong Shen, Xianglei Liu, Huan He, Weitao Wu, Baoan Liu

 PII:
 S0022-4073(17)30924-X

 DOI:
 10.1016/j.jqsrt.2018.02.030

 Reference:
 JQSRT 6011

To appear in: Journal of Quantitative Spectroscopy & Radiative Transfer

Received date:2 December 2017Revised date:24 January 2018Accepted date:26 February 2018

Please cite this article as: Jiadong Shen, Xianglei Liu, Huan He, Weitao Wu, Baoan Liu, Highperformance noncontact thermal diode via asymmetric nanostructures, *Journal of Quantitative Spectroscopy & Radiative Transfer* (2018), doi: 10.1016/j.jqsrt.2018.02.030

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



ACCEPTED MANUSCRIPT

Submitted to JQSRT, November 30th, 2017, revision submitted on January 24th, 2018

Highlights

- A photonic thermal diode based on asymmetric nanostructures is proposed.
- The rectification ratio is higher than that of planar bulks by over 10 times.
- Nanostructures have a higher forward radiative heat flux due to the lower loss.
- The reversed heat flow is inhabited due to smaller cut-off wavevectors.

A

Download English Version:

https://daneshyari.com/en/article/7846019

Download Persian Version:

https://daneshyari.com/article/7846019

Daneshyari.com