

Accepted Manuscript

Segregated conductive polymer composite with synergistically electrical and mechanical properties

Wei Zhai, Shuaiguo Zhao, Yan Wang, Guoqiang Zheng, Kun Dai, Chuntai Liu, Changyu Shen

PII: S1359-835X(17)30407-4

DOI: <https://doi.org/10.1016/j.compositesa.2017.11.008>

Reference: JCOMA 4829

To appear in: *Composites: Part A*

Received Date: 30 August 2017

Revised Date: 10 November 2017

Accepted Date: 12 November 2017



Please cite this article as: Zhai, W., Zhao, S., Wang, Y., Zheng, G., Dai, K., Liu, C., Shen, C., Segregated conductive polymer composite with synergistically electrical and mechanical properties, *Composites: Part A* (2017), doi: <https://doi.org/10.1016/j.compositesa.2017.11.008>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

Segregated conductive polymer composite with synergistically electrical and mechanical properties

Wei Zhai^a, Shuaiguo Zhao^a, Yan Wang^b, Guoqiang Zheng^a, Kun Dai^{a,*}, Chuntai Liu^{a,*},
Changyu Shen^a

^a*School of Materials Science and Engineering, The Key Laboratory of Material Processing and Mold of Ministry of Education, Zhengzhou University, Zhengzhou, Henan 450001, P.R. China*

^b*School of Textile and Material Engineering, Dalian Polytechnic University, Dalian 116034, P. R. China*

Abstract

The potential of segregated conductive polymer composites is greatly hampered due to its poor mechanical strength and brittle nature. In this work, plunger type injection molding (PTIM) is developed to achieve synergistically electrical and mechanical properties on carbon nanotubes (CNTs)/polypropylene (PP)/ultra-high molecular weight polyethylene (UHMWPE) segregated conductive polymer composite. Morphology observation indicates that the segregated CNTs conductive network was formed along the interfaces between PP and UHMWPE grains. An ultralow percolation threshold of 0.13 vol. % is achieved, which is much lower than that of conventional injection molding. The strength of PTIM sample is improved; importantly, more than 10 times of improvement in elongation at break has been achieved compared to the sample obtained from frequently-used compression molding. Stability of the segregated conductive

*Corresponding authors.

E-mail: kundai@zzu.edu.cn (K. Dai), ctliu@zzu.edu.cn (C. Liu)

Download English Version:

<https://daneshyari.com/en/article/7889758>

Download Persian Version:

<https://daneshyari.com/article/7889758>

[Daneshyari.com](https://daneshyari.com)