

## Accepted Manuscript

New analytical and numerical optical model for the laser assisted tape winding process

Jasper Reichardt, Ismet Baran, Remko Akkerman

PII: S1359-835X(18)30037-X

DOI: <https://doi.org/10.1016/j.compositesa.2018.01.029>

Reference: JCOMA 4910

To appear in: *Composites: Part A*

Received Date: 5 October 2017

Revised Date: 22 December 2017

Accepted Date: 25 January 2018



Please cite this article as: Reichardt, J., Baran, I., Akkerman, R., New analytical and numerical optical model for the laser assisted tape winding process, *Composites: Part A* (2018), doi: <https://doi.org/10.1016/j.compositesa.2018.01.029>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

# New analytical and numerical optical model for the laser assisted tape winding process

Jasper Reichardt<sup>1</sup>, Ismet Baran<sup>1\*</sup> and Remko Akkerman<sup>1</sup>

<sup>1</sup>*University of Twente, Faculty of Engineering Technology, NL-7500AE Enschede, The Netherlands*

*\*E-mail: I.Baran@utwente.nl*

---

## Abstract

New analytical and numerical optical models are proposed for the laser assisted tape winding (LATW) of thermoplastic composites. The irradiation and reflection of the laser beam directly influence the heat flux and temperature distribution during the consolidation, hence the laser optics must be described and understood well for improved bonding quality. For the first time, a two-dimensional (2D) analytical solution is derived for the laser light distribution and reflection by combining the principle of energy conservation with unpolarized Fresnel equations. In the more comprehensive numerical model, a 3D ray tracing approach is incorporated in which a novel non-specular reflection model is developed predicting the anisotropic reflective behaviour of the composite. Heat flux distributions for the substrate and incoming tape are calculated. The analytical and numerical model results are shown to correspond. The non-specular and scattering reflection yields in a larger illuminated area with lower intensity for substrate and tape.

*Keywords:* A. Polymer-matrix composites (PMCs); C. Analytical modelling; C. Computational modelling; E. Tape; Laser assisted tape winding

---

## 1. Introduction

Laser assisted tape winding (LATW) is an automated process to produce tubular or tube-like continuous fibre-reinforced parts by winding a tape around a mandrel or liner. A schematic view of the process, which is very similar to laser assisted tape placement (LATP), is depicted in Fig. 1. The thermoplastic tapes are deposited onto a substrate

Download English Version:

<https://daneshyari.com/en/article/7889928>

Download Persian Version:

<https://daneshyari.com/article/7889928>

[Daneshyari.com](https://daneshyari.com)