## Accepted Manuscript

Fracture toughness distribution of alumina-titanium functionally graded materials fabricated by spark plasma sintering

Tomoyuki Fujii, Keiichiro Tohgo, Masahiro Iwao, Yoshinobu Shimamura

PII: S0925-8388(18)32425-3

DOI: 10.1016/j.jallcom.2018.06.304

Reference: JALCOM 46640

To appear in: Journal of Alloys and Compounds

Received Date: 25 April 2018

Revised Date: 23 June 2018

Accepted Date: 25 June 2018

Please cite this article as: T. Fujii, K. Tohgo, M. Iwao, Y. Shimamura, Fracture toughness distribution of alumina-titanium functionally graded materials fabricated by spark plasma sintering, *Journal of Alloys and Compounds* (2018), doi: 10.1016/j.jallcom.2018.06.304.

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



## Fracture toughness distribution of alumina-titanium functionally graded materials fabricated by spark plasma sintering

Tomoyuki Fujii<sup>\*1</sup>, Keiichiro Tohgo<sup>1</sup>, Masahiro Iwao<sup>1</sup>, and Yoshinobu Shimamura<sup>1</sup>

<sup>1</sup> Department of Mechanical Engineering, Shizuoka University 3-5-1, Johoku, Naka-ku, Hamamatsu 432-8561, Japan

\*Corresponding author: Dr. T. Fujii

e-mail: fujii.tomoyuki@shizuoka.ac.jp Tel & Fax: +81-53-478-1029 Download English Version:

## https://daneshyari.com/en/article/7990309

Download Persian Version:

https://daneshyari.com/article/7990309

Daneshyari.com