



# Asymptotic frequencies of various damped nonlocal beams and plates



Y. Lei<sup>a</sup>, S. Adhikari<sup>b</sup>, T. Murmu<sup>c,\*</sup>, M.I. Friswell<sup>b</sup>

<sup>a</sup> College of Aerospace and Material Engineering, National University of Defence Technology, Changsha, Hunan 410073, PR China

<sup>b</sup> College of Engineering, Swansea University, Singleton Park, Swansea SA2 8PP, UK

<sup>c</sup> School of Engineering, University of the West of Scotland, Paisley PA12BE, UK

## ARTICLE INFO

### Article history:

Received 3 September 2013

Accepted 6 August 2014

Available online 27 August 2014

### Keywords:

Asymptotic frequencies

Viscoelastic

Nonlocal elasticity

Euler–Bernoulli beam

Timoshenko beam

Kirchhoff plate

Mindlin plate

Damping

## ABSTRACT

A striking difference between the conventional local and nonlocal dynamical systems is that the later possess finite asymptotic frequencies. The asymptotic frequencies of four kinds of nonlocal viscoelastic damped structures are derived, including an Euler–Bernoulli beam with rotary inertia, a Timoshenko beam, a Kirchhoff plate with rotary inertia and a Mindlin plate. For these undamped and damped nonlocal beam and plate models, the analytical expressions for the asymptotic frequencies, also called the maximum or escape frequencies, are obtained. For the damped nonlocal beams or plates, the asymptotic critical damping factors are also obtained. These quantities are independent of the boundary conditions and hence simply supported boundary conditions are used. Taking a carbon nanotube as a numerical example and using the Euler–Bernoulli beam model, the natural frequencies of the carbon nanotubes with typical boundary conditions are computed and the asymptotic characteristics of natural frequencies are shown.

© 2014 Elsevier Ltd. All rights reserved.

## 1. Introduction

Structures at the nano-scale dimension are subject to damping from external forces, such as magnetic forces (Lee and Lin, 2010), interaction with the substrate, humidity and thermal effects (Chen et al., 2011), and fluid damping (Bhiladvala and Wang, 2004). The Akhiezer damping phenomenon is found in nanostructures such as a nano-mechanical resonator with a nearly uniform strain field (Kunal and Aluru, 2011). The general characteristics of the damping may be elastic or viscoelastic and these characteristics play a vital role in the dynamic analysis of structures. At the nano-scale, the understanding of damping characteristics, for example in atomic force microscopes (AFM), is required to generate superior image quality at high scan rates. Further, damping at the nano-scale is important for vibration based nano-sensors (Adhikari and Chowdhury, 2012) for the accurate measurement of the frequency shift. Damping mechanisms are usually complex and often approximated as proportional damping in engineering applications, with the damping parameters found from experiment. Calleja et al. (2012) stated that accurate quantification of the damping is vital to understand the sensitivity of nano-scale mass sensors. Hence, the investigation of the dynamic response of damped beams and plates at the nano-scale is essential.

The development of nano-technology yields an increasing number of nano-scale devices, including nano-electro-mechanical systems (NEMS) and micro-electro-mechanical systems (MEMS). Basic structural elements such as beams and plates at the nano-scale are utilized as nano-structure components for NEMS and MEMS. Widely used nano-rods and nano-beams include carbon and boron nitride nanotubes, while popular nano-plates (i.e. two-dimensional structures) are graphene sheets and gold nano-plates. Two key computational methodologies available for the dynamic analysis of these nano-structures comprise molecular dynamic (MD) simulation and continuum mechanics based approaches. Both of these methods have drawbacks. Some realistic experiments are available, although controlling every parameter at the nano-scale is difficult. Continuum mechanics is gaining popularity, although the size and scale effects are important at the nano-scale, and cannot be ignored. Among the size-dependent mechanics methods, the nonlocal continuum model (Eringen, 1983) has received significant interest in recent years. By employing the nonlocal elasticity approach, length-scale effects may be included in a simple, but physically understandable, way in nano-structures. The nonlocal continuum theory has been compared with molecular dynamics simulations, and excellent agreement has been obtained (Ansari and Sahmani, 2012; Ansari et al., 2010; Murmu and Adhikari,

\* Corresponding author. Tel.: +44 0141 848 3235.

E-mail address: [murmutony@gmail.com](mailto:murmutony@gmail.com) (T. Murmu).

2011). Nonlocal Euler–Bernoulli and Timoshenko beam models have been used for bending, vibration and buckling analysis of nanostructures (Ansari and Ramezannezhad, 2011; Benzair et al., 2008; Heireche et al., 2008; Li et al., 2011; Murmu and Adhikari, 2010; Murmu and Pradhan, 2009; Reddy, 2007; Reddy and Pang, 2008; Simsek, 2011; Thai, 2012; Yang et al., 2011, 2012). Lu et al. (2007) proposed nonlocal elastic plate theories. Nonlocal beam and plate models are widely used for carbon nano-tubes and graphene (Arash and Wang, 2012).

In this communication we consider viscoelastic damped nonlocal structures. The effect of viscoelastic damping on the vibration response has been investigated by several researchers. Lopez and Fernandez (2012) considered nonlocal viscoelastic damping patches in the bending vibrations of Euler–Bernoulli beams. The dynamics of Euler–Bernoulli beams and Kirchhoff plates with nonlocal damping, including time and hysteresis effects has been investigated (Friswell et al., 2007; Lei et al., 2006). Using the finite element method developed for nonlocal viscoelastic beam models, Friswell et al. (2007) studied the dynamics of beams with different boundary conditions. Although these investigations highlighted the role of viscoelasticity for macro-scale models, their applicability to the nano-scale remains an open question.

The appearance of asymptotic frequencies for nanostructures, using nonlocal mechanics, have been reported, including wave propagation in carbon nano-tubes via nonlocal continuum mechanics models (Wang, 2005). The derivation of asymptotic phase velocities and frequencies were presented. The asymptotic frequency is important as the scale coefficient or nonlocal parameter could be obtained from its known or measured value. Wang and Varadan (2007) performed similar work with nonlocal shell theory and estimated the scale coefficient based on the derived asymptotic frequency. Escape frequencies or asymptotic frequencies were also proposed for embedded graphene sheets (Narendar and Gopalakrishnan, 2012). The relationships between the asymptotic frequencies and the nonlocal scaling parameter were established.

The literature survey clearly shows that most studies investigating asymptotic frequencies on scale-dependent beams and plates considered undamped structures, and work on damped structures is very limited. For nonlocal elastic solids, asymptotic frequencies exist, in contrast to local elastic solids. In this communication, the asymptotic frequencies and asymptotic critical damping factors are derived and presented for four kinds of nonlocal viscoelastic damped structures. These structural elements include Euler–Bernoulli beams with rotary inertia, Timoshenko beams, Kirchhoff plates with rotary inertia, and Mindlin plates. Kirchhoff plate theory is a thin plate theory that ignores the effect of transverse shear deformation. Mindlin plate theory is a first-order shear-deformable plate theory, where the transverse shear deformation is significant in thick plates and shear-deformable plates. These structures may be applied to the nano-scale, including nonlocal effects. The asymptotic frequencies form an upper bound for the natural frequencies of these structures. The higher frequency mode shapes are not significantly affected by the boundary conditions of the structures; that is the asymptotic frequencies are equal for all boundary conditions for a given beam or plate theory. Hence simply supported boundary conditions are used to calculate the asymptotic frequencies (also called the maximum or escape frequencies) for the undamped and damped nonlocal beams and plates, as analytical solutions are most easily obtained for these boundary conditions. For the damped nonlocal beams or plates, the asymptotic critical damping factors are also obtained. A carbon nano-tube is taken as a numerical example, and using the Timoshenko beam model, the natural frequencies of the carbon nano-tubes with typical boundary conditions are computed, and the asymptotic characteristics of the natural frequencies are highlighted.

## 2. Equations of motion for damped nonlocal beams and plates

Lu et al. (2007) gave a brief review of nonlocal elasticity theory, and basic nonlocal beam and plate theories are reported in the literature (for example, Arash and Wang, 2012). According to nonlocal elasticity theory, the stress tensor at a point  $\mathbf{r}$  is given by

$$\sigma = \int_V K(|\mathbf{r}' - \mathbf{r}|, \tau) \sigma_m(\mathbf{r}') d\mathbf{r}' \quad (1)$$

where  $K$  is the nonlocal modulus,  $|\mathbf{r}' - \mathbf{r}|$  is the Euclidean distance and  $\sigma_m$  is the local macroscopic stress. The term  $\tau$  is the material constant that depends on the internal and external lengths. Eq. (1) is in integral partial form and the resulting integro-partial differential equation is difficult to solve. For certain choices of the kernel function, this equation may be transformed into an easier differential form (Eringen, 1983; Reddy, 2007), for example

$$(1 - \tau^2 \nabla^2) \sigma = \sigma_m, \quad \tau = \frac{e_0 a}{l} \quad (2)$$

where  $e_0$  is a material constant,  $a$  and  $l$  denote the internal and external characteristic lengths, respectively.

Incorporating the nonlocal effects (Eringen, 1983), external damping, initial pre-stress and the Kelvin-Voigt viscoelastic model (or internal damping) into nano-beam and nano-plate models, the governing equations for the vibration analysis of different systems are obtained. The details of the derivation for beams is discussed in an earlier paper by the present authors (Lei et al., 2013a). Using Eq. (2) we list the equation of motion for four systems discussed in this communication.

### 2.1. Nonlocal viscoelastic Euler–Bernoulli beam with rotary inertia

Consider an Euler–Bernoulli beam with deflection  $w$ , at position  $x$  along the beam. Then we have the following equations:

$$\left(1 + \tau_d \frac{\partial}{\partial t}\right) EI \frac{\partial^4 w}{\partial x^4} + \rho A \left[1 - (e_0 a)^2 \frac{\partial^2}{\partial x^2}\right] \frac{\partial^4 w}{\partial t^2} + C_1 \left[1 - (e_0 a)^2 \frac{\partial^2}{\partial x^2}\right] \frac{\partial w}{\partial t} - \rho I \left[1 - (e_0 a)^2 \frac{\partial^2}{\partial x^2}\right] \frac{\partial^4 w}{\partial x^2 \partial t^2} + N_0 \left[1 - (e_0 a)^2 \frac{\partial^2}{\partial x^2}\right] \frac{\partial^2 w}{\partial x^2} = 0, \quad (3)$$

where  $E, I, \rho, A$  are Young's modulus, second moment of area, density and cross-sectional area of the beam.  $N_0$  is the axial pre-stress.  $t$  denotes the time and  $\tau_d$  is the viscoelastic time constant.  $C_1$  is the displacement–velocity–dependent viscous damping coefficient. The term  $e_0 a$  is the nonlocal parameter where  $a$  is the external characteristic length such as crack length, wavelength or sample length. The dynamics of a damped viscoelastic nonlocal Euler–Bernoulli beam was described by Lei et al. (2013b).

Download English Version:

<https://daneshyari.com/en/article/800840>

Download Persian Version:

<https://daneshyari.com/article/800840>

[Daneshyari.com](https://daneshyari.com)