Accepted Manuscript

Development and Assessment of Integrating Parabolic Trough Collectors with Gas Turbine Trigeneration System for Producing Electricity, Chilled Water, and Freshwater

Yousef N. Dabwan, Pei Gang, Jing Li, Guangtao Gao, Junsheng Feng

PII: S0360-5442(1)	3)31508-1
--------------------	-----------

DOI: 10.1016/j.energy.2018.07.211

Reference: EGY 13476

To appear in: Energy

Received Date: 14 April 2018

Accepted Date: 31 July 2018

Please cite this article as: Yousef N. Dabwan, Pei Gang, Jing Li, Guangtao Gao, Junsheng Feng, Development and Assessment of Integrating Parabolic Trough Collectors with Gas Turbine Trigeneration System for Producing Electricity, Chilled Water, and Freshwater, *Energy* (2018), doi: 10.1016/j.energy.2018.07.211

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



1	Development and Assessment of Integrating Parabolic Trough Collectors with Gas
2	Turbine Trigeneration System for Producing Electricity, Chilled Water, and
3	Freshwater
4	Yousef N. Dabwan ^{a,b} , Pei Gang ^{a*} , Jing Li ^{a,c} , Guangtao GAO ^a , Junsheng FENG ^a .
5	^a Department of Thermal Science and Energy Engineering, University of Science and Technology of
6	China, 96 Jinzhai Road, Hefei, China
7	^b Department of Mechanical Engineering, Sana'a University, Sana'a, Yemen.
8	^c Institute of Sustainable Energy Technology, University of Nottingham, University Park, Nottingham
9	NG7 2RD, UK
10	* Corresponding author. Tel./Fax: +86 0551 63601652. E-mail address: peigang@ustc.edu.cn;
11	

12 ABSTRACT

13 The main objective of the present work is to investigate the possible modifications of a gas turbine 14 trigeneration plant via integrating it with a parabolic trough collector (PTC) technology. This plant produces 45461 m³/day of freshwater and 2300 kg/s of chilled water in addition to producing 360 15 16 MWe of electricity (the steam turbines yield 110 MWe). The annual performance of an integrated 17 solar gas turbine trigeneration power plant (ISGTPP) with different sizes of gas turbine and solar 18 collector's area have been examined using Thermoflex software under Al-Hodeidah (Yemen) 19 weather conditions. This study revealed that the ISGTPP results in a minor increase in levelized 20 electricity cost (LEC) compared to the conventional trigeneration plant, nevertheless it reduces the 21 LEC by 62–71.5% relative to the fully-solar-powered PTC power plants. Moreover, the study 22 identified the configuration of ISGTPP with a gas turbine of 130 MWe capacity and 39.7 hectares of 23 PTC's total aperture area as the most optimal engine configuration. It reduces the annual CO₂ 24 emissions by 385 k-tonne (30.2%) in comparing with that emitted by the reference plant with a gas 25 turbine of 250 MWe size and 100 k-tonne (10%) compared with that emitted by the corresponding conventional plant with 130 MWe size. 26

27

Download English Version:

https://daneshyari.com/en/article/8070778

Download Persian Version:

https://daneshyari.com/article/8070778

Daneshyari.com