

Accepted Manuscript

A continuous concentration gradient flow electrical energy storage system based on reverse osmosis and pressure retarded osmosis

Rui Long, Xiaotian Lai, Zhichun Liu, Wei Liu

PII: S0360-5442(18)30626-1

DOI: [10.1016/j.energy.2018.04.022](https://doi.org/10.1016/j.energy.2018.04.022)

Reference: EGY 12661

To appear in: *Energy*

Received Date: 4 December 2017

Revised Date: 2 April 2018

Accepted Date: 5 April 2018

Please cite this article as: Long R, Lai X, Liu Z, Liu W, A continuous concentration gradient flow electrical energy storage system based on reverse osmosis and pressure retarded osmosis, *Energy* (2018), doi: 10.1016/j.energy.2018.04.022.

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



A continuous concentration gradient flow electrical energy storage system based on reverse osmosis and pressure retarded osmosis

Rui Long*, Xiaotian Lai, Zhichun Liu, and Wei Liu*

School of Energy and Power Engineering, Huazhong University of Science and Technology,
1037 Luoyu Road, Wuhan 430074, China

*Corresponding authors:

Tel: +86-27-87542618

Fax: +86-27-87540724

E-mail addresses: r_long@hust.edu.cn (R. Long), w_liu@hust.edu.cn (W. Liu)

Abstract

A continuous concentration gradient flow electrical energy storage system is presented to store the electricity generated by the renewable energy power, which consists of reverse osmosis, generating concentrated salty streams under the external power input, and pressure retarded osmosis, extracting electricity from the produced Gibbs free energy of mixing. The hybrid system is simulated on the module scale under the perfect membrane assumption. The operation parameters that impact the overall performance of the proposed system are systematically investigated. Results reveal that there exist optimal reverse osmosis and pressure retarded osmosis operation pressures leading to a maximum round-trip energy efficiency under given feed solution distribution factor. The distinct thermodynamically limiting operation regimes are identified based on analytical calculation. In the feed limited regime (FLR), a round-trip energy efficiency of 38.27% has been achieved, indicating its

Download English Version:

<https://daneshyari.com/en/article/8071707>

Download Persian Version:

<https://daneshyari.com/article/8071707>

[Daneshyari.com](https://daneshyari.com)