



# Comprehensive analysis and parametric optimization of a CCP (combined cooling and power) system driven by geothermal source



Yajing Zhao <sup>a</sup>, Jiangfeng Wang <sup>a,\*</sup>, Liyan Cao <sup>a</sup>, Yu Wang <sup>b</sup>

<sup>a</sup> Institute of Turbomachinery, State Key Laboratory of Multiphase Flow in Power Engineering, School of Energy and Power Engineering, Xi'an Jiaotong University, Xi'an 710049, China

<sup>b</sup> Department of Mechanical Engineering, Stanford University, Stanford, CA 94305, USA

## ARTICLE INFO

### Article history:

Received 16 September 2015

Received in revised form

31 December 2015

Accepted 3 January 2016

Available online xxx

### Keywords:

Exergoeconomic analysis

Exergy analysis

Geothermal energy

CCP

Optimization

## ABSTRACT

A CCP (combined cooling and power) system, which integrated a flash-binary power generation system with a bottom combined cooling and power subsystem operating through the combination of an organic Rankine cycle and an ejector refrigeration cycle, was developed to utilize geothermal energy. Thermodynamic and exergoeconomic analyses were performed on the system. A performance indicator, namely the average levelized costs per unit of exergy products for the overall system, was developed to assess the exergoeconomic performance of the system. The effects of four key parameters including flash pressure, pinch point temperature difference in the vapor generator, inlet pressure and back pressure of the ORC turbine on the system performance were evaluated through a parametric analysis. Two single-objective optimizations were conducted to reach the maximum exergy efficiency and the minimum average levelized costs per unit of exergy products for the overall system, respectively. The optimization results implied that the most exergoeconomically effective system couldn't obtain the best system thermodynamic performance and vice versa. An exergy analysis based on the thermodynamic optimization result revealed that the biggest exergy destruction occurred in the vapor generator and the next two largest exergy destruction were respectively caused by the steam turbine and the flashing device.

© 2016 Elsevier Ltd. All rights reserved.

## 1. Introduction

The demand for energy is growing at an increasing rate due to the growth of population, and is arousing wide concerns about the security of energy supply for the long term [1]. Energy resources have been divided into three categories: fossil fuels, renewable resources and nuclear resources [2]. Using fossil fuels can result in environmental deterioration and resource depletion. Nuclear energy can cause serious problems for the environment and human health. Renewable energy sources, which are sustainable and environmental friendly, are hence under emerging exploitation [3]. Among all kinds of renewable energies, geothermal energy, which has abundant amount of storage [4] as well as significant base-load potential [1], is expected to make an increasing contribution for energy supply in a near future [5].

\* Corresponding author. Institute of Turbomachinery, State Key Laboratory of Multiphase Flow in Power Engineering, Xi'an Jiaotong University, No.28 Xianning West Road, Xi'an 710049, China. Tel./fax: +86 029 82668704.

E-mail address: [jfwang@mail.xjtu.edu.cn](mailto:jfwang@mail.xjtu.edu.cn) (J. Wang).

Variety of thermal systems have been developed to utilize geothermal energy. Conventional power systems that simply converted geothermal energy into electricity have been widely studied since 1904 when a dry-steam geothermal power system was first built and operated in the Tuscany region of Italy [6]. Although dry-steam power systems can utilize the dry geothermal steam directly to produce electricity, dry steam reservoirs are rare and only found in few fields around the world while most of the remaining conventional geothermal fields worldwide are wet fields [7]. Hence, more attention has been paid to other types of power systems including single-flash steam power systems, double-flash steam power systems, binary cycle power systems and flash-binary power systems to develop wet geothermal fields for power generation [8–12]. Particularly, for temperature of the geothermal water below 180 °C where direct flashing processes are not suitable anymore [13], ORC (organic Rankine cycle) and Kalina cycle, both of which are well proven and reliable technologies for energy conversion, especially for exploiting low-temperature heat sources, have been widely applied as the subsystem in binary cycle power systems [10–12,14–20]. However, conventional power plants can

**Nomenclature**

|                        |                                                                                                           |
|------------------------|-----------------------------------------------------------------------------------------------------------|
| $A$                    | cross sectional area ( $\text{m}^2$ ); heat exchanger area ( $\text{m}^2$ )                               |
| $Bo$                   | boiling number                                                                                            |
| $\dot{C}$              | cost rates ( $\text{\$ year}^{-1}$ )                                                                      |
| $\dot{C}_{\text{dif}}$ | fictitious cost rates associated with dissipative components ( $\text{\$ year}^{-1}$ )                    |
| $CEPCI$                | chemical engineering plant cost index                                                                     |
| $CRF$                  | capital recovery factor                                                                                   |
| $c$                    | levelized costs per unit of exergy ( $\text{\$ (MWh)}^{-1}$ )                                             |
| $c_p$                  | specific heat ( $\text{J kg}^{-1} \text{K}^{-1}$ )                                                        |
| $D$                    | diameter (m)                                                                                              |
| $\dot{E}$              | annual exergy transfer rates ( $\text{J year}^{-1}$ )                                                     |
| $\dot{E}_x$            | exergy flow rates ( $\text{J s}^{-1}$ )                                                                   |
| $ex$                   | specific exergy ( $\text{J kg}^{-1}$ )                                                                    |
| $F$                    | factor                                                                                                    |
| $f$                    | friction factor                                                                                           |
| $G$                    | mass velocity ( $\text{kg m}^{-2} \text{s}^{-1}$ )                                                        |
| $h$                    | enthalpy ( $\text{J kg}^{-1}$ ); convection heat transfer coefficient ( $\text{W m}^{-2} \text{K}^{-1}$ ) |
| $i_{\text{eff}}$       | effective discount (%)                                                                                    |
| $K$                    | constant                                                                                                  |
| $L$                    | length (m)                                                                                                |
| $l_B$                  | baffle spacing (m)                                                                                        |
| $\dot{M}$              | mass flow rates ( $\text{kg s}^{-1}$ )                                                                    |
| $N$                    | number of the tubes                                                                                       |
| $n$                    | lifetime (year)                                                                                           |
| $Nu$                   | Nusselt number                                                                                            |
| $P$                    | pressure (bar)                                                                                            |
| $Pr$                   | Prandtl number                                                                                            |
| $P_t$                  | distance between tubes (m)                                                                                |
| $Q_{vs}$               | volumetric stream flow ( $\text{m}^3 \text{s}^{-1}$ )                                                     |
| $\dot{Q}$              | heat transfer rate (W)                                                                                    |
| $q_m$                  | average imposed wall heat flux ( $\text{W m}^{-2}$ )                                                      |
| $Re$                   | Reynolds number                                                                                           |
| $r$                    | enthalpy of vaporization ( $\text{J kg}^{-1}$ )                                                           |
| $s$                    | specific entropy ( $\text{J kg}^{-1} \text{K}^{-1}$ )                                                     |
| $T$                    | temperature (K)                                                                                           |
| $t$                    | working hours (hours)                                                                                     |
| $U$                    | overall heat transfer coefficient ( $\text{W m}^{-2} \text{K}^{-1}$ )                                     |
| $V$                    | volume ( $\text{m}^3$ )                                                                                   |
| $v_t$                  | terminal velocity ( $\text{m s}^{-1}$ )                                                                   |
| $\dot{W}$              | power (W)                                                                                                 |
| $x$                    | vapor quality                                                                                             |
| $y$                    | exergy destruction ratio (%)                                                                              |
| $\dot{Z}$              | annually levelized cost value ( $\text{\$ year}^{-1}$ )                                                   |

**Greek letters**

|               |                                                                            |
|---------------|----------------------------------------------------------------------------|
| $\delta$      | thickness (m)                                                              |
| $\Delta t_m$  | logarithmic mean temperature difference between hot side and cold side (K) |
| $\varepsilon$ | component exergy efficiency (%)                                            |
| $\eta$        | efficiency (%)                                                             |
| $\lambda$     | thermal conductivity ( $\text{W m}^{-1} \text{K}^{-1}$ )                   |

|        |                                                |
|--------|------------------------------------------------|
| $\rho$ | density ( $\text{kg/m}^3$ )                    |
| $\mu$  | viscosity ( $\text{kg s}^{-1} \text{m}^{-1}$ ) |

**Subscripts**

|         |                                                |
|---------|------------------------------------------------|
| A       | upper part                                     |
| B       | lower part                                     |
| BM      | bare module                                    |
| cond    | condenser                                      |
| cond1   | condenser 1                                    |
| cond2   | condenser 2                                    |
| D       | destruction                                    |
| elec    | electricity                                    |
| es      | equivalent diameter                            |
| evap    | evaporator                                     |
| ex      | exergy                                         |
| F       | fuel                                           |
| he      | heat exchanger                                 |
| $i,j,k$ | state points                                   |
| i       | inside                                         |
| in      | inlet                                          |
| ip      | inlet pipe                                     |
| L       | loss                                           |
| l       | liquid                                         |
| M       | material factor                                |
| m       | mean                                           |
| max     | maximum                                        |
| min     | minimum                                        |
| o       | outside                                        |
| out     | outlet                                         |
| P       | product; pressure factor                       |
| pump    | pump                                           |
| pump1   | pump 1                                         |
| pump2   | pump 2                                         |
| q       | heat transfer; cold exergy output              |
| ref     | reference period                               |
| s       | single-phase                                   |
| ss      | shell-side                                     |
| sep     | separator                                      |
| system  | exergy products produced by the overall system |
| th      | thermal                                        |
| tot     | total                                          |
| ts      | tube-side                                      |
| turb    | turbine                                        |
| turb1   | steam turbine                                  |
| turb2   | ORC turbine                                    |
| v       | vapor                                          |
| vg      | vapor generator                                |
| w       | power                                          |
| well    | drilling wells                                 |
| wt1     | power produced by steam turbine                |
| wt2     | power produced by ORC turbine                  |
| y       | per year                                       |
| 0       | ambient state                                  |
| 1–23    | state points                                   |

only produce electricity and are not adequate for meeting with diverse consumers' requirements for energy supply. To satisfy the diverse users' demands and to utilize the energy source more efficiently, some cogeneration systems that combines electricity generation with other kinds of energy production have been

developed for the exploiting of low- or medium-temperature heat sources such as geothermal water. A number of studies on geothermal cogeneration systems have been concentrated on the CHP (combined heat and power) technologies, which are relatively mature technologies directly using the geothermal water

Download English Version:

<https://daneshyari.com/en/article/8074331>

Download Persian Version:

<https://daneshyari.com/article/8074331>

[Daneshyari.com](https://daneshyari.com)