Accepted Manuscript

Modelling and Analysis of selected OECD PKL3 Station-Blackout Experiments using TRACE

Roman Mukin, Ivor Clifford, Omar Zerkak, Hakim Ferroukhi

PII: \$1738-5733(17)30572-7

DOI: 10.1016/j.net.2017.12.005

Reference: NET 473

To appear in: Nuclear Engineering and Technology

Received Date: 15 September 2017 Revised Date: 13 November 2017 Accepted Date: 16 December 2017

Please cite this article as: R. Mukin, I. Clifford, O. Zerkak, H. Ferroukhi, Modelling and Analysis of selected OECD PKL3 Station-Blackout Experiments using TRACE, *Nuclear Engineering and Technology* (2018), doi: 10.1016/j.net.2017.12.005.

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



Modelling and Analysis of selected OECD PKL3 Station-Blackout Experiments using TRACE

Roman Mukin¹, Ivor Clifford, Omar Zerkak and Hakim Ferroukhi

Paul Scherrer Institute 5232 Villigen PSI, Switzerland

ABSTRACT

Series of tests dedicated to Station-Blackout (SBO) accident scenarios have been recently performed at the PKL facility in the framework of the OECD/NEA PKL 3 Project. These investigations address current safety issues related to beyond design basis accident transients with significant core heat-up. This work presents a detailed analysis using the best-estimate thermal-hydraulic code TRACE (v5.0 Patch4) of different SBO scenarios conducted at the PKL facility; failures of high and low-pressure safety injection systems together with steam generator (SG) feedwater supply are considered, thus calling for adequate accident management (AM) actions and timely implementation of alternative emergency cooling procedures to prevent core meltdown. The presented analysis evaluates the capability of the applied TRACE model of the PKL facility to correctly capture the sequences of events in the different SBO scenarios, namely the SBO tests H2.1, H2.2 run 1 and H2.2 run 2, including symmetric or asymmetric secondary side depressurization (SDE), primary side depressurization (PDE), accumulator (ACC) injection in the cold legs and secondary side feeding with mobile pump and/or primary side emergency core cooling (ECC) injection from the fuel pool cooling pump (FPCP). This study is focused specifically on the prediction of the Core Exit Temperature (CET), which drives the execution of the most relevant AM actions. This work presents, in particular, the key improvements made to the TRACE model that helped to improve the code predictions, including the modelling of dynamical heat losses, the nodalization of SGs' heat exchanger tubes and the ACCs. Another relevant aspect of this work is to evaluate how well the model simulations of the three different scenarios qualitatively and quantitatively capture the trends and results exhibited by the actual experiments. For instance; how the number of SGs considered for SDE affects the heat transfer from primary side; how the discharge capacity of the pressurizer relief valve affects the dynamics of the transient; how ACC initial pressure and nitrogen release affect the grace time between ACC injection and subsequent core heat up; and how well the alternative feeding modes of the secondary and/or primary side with mobile injection pumps affect core quenching and ensure stable long-term core cooling under controlled boiling conditions.

KEYWORDS

Station black-out, TRACE, validation, PKL, PCT, CET

-

¹ Corresponding author: Roman Mukin, e-mail: roman.mukin@psi.ch

Download English Version:

https://daneshyari.com/en/article/8083765

Download Persian Version:

https://daneshyari.com/article/8083765

Daneshyari.com