


Accepted Manuscript

Life cycle impact comparison of different concrete floor slabs considering uncertainty and sensitivity analysis

JingJing Wang, Danielle Densley Tingley, Martin Mayfield, YuanFeng Wang



PII: S0959-6526(18)31114-4
DOI: 10.1016/j.jclepro.2018.04.094
Reference: JCLP 12675
To appear in: *Journal of Cleaner Production*
Received Date: 14 October 2017
Revised Date: 06 April 2018
Accepted Date: 10 April 2018

Please cite this article as: JingJing Wang, Danielle Densley Tingley, Martin Mayfield, YuanFeng Wang, Life cycle impact comparison of different concrete floor slabs considering uncertainty and sensitivity analysis, *Journal of Cleaner Production* (2018), doi: 10.1016/j.jclepro.2018.04.094

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

Life cycle impact comparison of different concrete floor slabs considering uncertainty and sensitivity analysis

JingJing Wang^{a,b}, Danielle Densley Tingley^b, Martin Mayfield^b, YuanFengWang^{a,*}

^{a,*}School of Civil Engineering, Beijing Jiaotong University, Beijing 100044, PR China.

^bDepartment of Civil and Structural Engineering, The University of Sheffield, S1 3JD, United Kingdom.

E-mail: cyfwang@bjtu.edu.cn. Tel: 86-10-51685552. Fax: 86-10-51685552.

Highlights:

Environmental impacts of precast, composite and cast-in-situ slabs are conducted.

All life cycle stages from cradle-to-grave (including end-of-life stage) are included.

Both midpoint and endpoint of LCA results are analyzed.

The floor slabs are designed based on two functional units.

Uncertainty analysis and sensitivity analysis are carried out.

Abstract:

The traditional construction industry is characterized as a labor-intensive, wasteful, and inefficient sector. Currently, prefabrication has become a common practice in residential development and has reduced energy consumption and waste generation compared to traditional on-site practices. This study investigates the differences in life cycle environmental impacts among three different floor systems (precast slab, composite slab (semi-precast slab) and cast-in-situ slab) based on two functional units (delivering the same carrying capacity and maintaining consistent floor depth) using both LCA midpoint and endpoint methods using the software tool SimaPro. This study sets a calculation boundary for the construction process: raw material production, slab production, transportation, construction activities on-site, demolition and recycling of buildings at the end-of-life stage. Moreover, uncertainty and sensitivity analysis are carried out to help decision-makers identify major environmental impact factors and develop eco-friendly plans to facilitate housing industrialization. The results indicate that (1) the environmental impact of precast slab outperforms those of cast-in-situ and composite floors regardless of different design functional units and evaluation methods. (2) While under different functional units, the environmental performance of composite and cast-in-situ floors varies considerably. (3) From the

Download English Version:

<https://daneshyari.com/en/article/8095154>

Download Persian Version:

<https://daneshyari.com/article/8095154>

[Daneshyari.com](https://daneshyari.com)