

Accepted Manuscript

Industrial wastewater treatment in constructed wetlands packed with construction materials and agricultural by-products

Tanveer Saeed, Sidratul Muntaha, Mamunur Rashid, Guangzhi Sun, Ariful Hasnat



PII: S0959-6526(18)31142-9

DOI: [10.1016/j.jclepro.2018.04.115](https://doi.org/10.1016/j.jclepro.2018.04.115)

Reference: JCLP 12696

To appear in: *Journal of Cleaner Production*

Received Date: 28 November 2017

Revised Date: 19 March 2018

Accepted Date: 12 April 2018

Please cite this article as: Saeed T, Muntaha S, Rashid M, Sun G, Hasnat A, Industrial wastewater treatment in constructed wetlands packed with construction materials and agricultural by-products, *Journal of Cleaner Production* (2018), doi: 10.1016/j.jclepro.2018.04.115.

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

INDUSTRIAL WASTEWATER TREATMENT IN CONSTRUCTED WETLANDS PACKED WITH CONSTRUCTION MATERIALS AND AGRICULTURAL BY- PRODUCTS

Tanveer Saeed^a, Sidratul Muntaha^a, Mamunur Rashid^a, Guangzhi Sun^b, Ariful Hasnat^a

^aDepartment of Civil Engineering, University of Asia Pacific, Dhaka, Bangladesh.

^bSchool of Engineering, Edith Cowan University, Joondalup WA 6027, Australia.

*Corresponding Author: tanveer@alumni.ait.asia;dr.tanveer@uap-bd.edu.

PABX: +8802-58157091-4,6; FAX:+8802-58157097

ABSTRACT

This paper reports pollutant removal performances from mixed industrial wastewater employing subsurface flow constructed wetland systems in Bangladesh. Two parallel hybrid wetland trains were established; each train included a vertical flow (VF) followed by a horizontal flow (HF) wetland. One hybrid system was packed with construction materials (i.e. recycled bricks), whereas the other system included agricultural by-products (i.e. sugarcane bagasse). All wetland units were planted with *Canna indica*. The hybrid trains were operated under non recirculation and recirculation phases; input hydraulic loading across each VF system ranged between 219.3-438.0 mm/d. Mean nitrogen, organics, solids, phosphorus and color removals across the hybrid systems were 67.5-80.0, 74.0-85.0, 55.0-95.0, 64.0-89.0 and 46.0-83.0% respectively. Lower input biodegradation ratio influenced organics removal routes in wetland systems that employed recycled bricks. In contrast, organic contents of sugarcane bagasse material supported microbial routes in the other system. VF wetland with organic media achieved higher TN removal rates (1.82 g/m² d), due to internal carbon (C) generation. Higher phosphorus removals (89.0%) were observed in hybrid system packed with recycled brick media, due to adsorption process. HF wetland packed with recycled brick was efficient in removing color compounds, whereas the other HF system (with organic media) showed high sulfate removals. Nitrogen and BOD removal improvement was observed in VF wetland (packed with recycled brick media) during recirculation period; in contrast, effluent recirculation reduced removal rates of such pollutants in VF system that employed organic media. In general, this study shows potential application of particular materials as the main media of wetland systems, to achieve pollutant removals from industrial wastewaters in Bangladesh.

KEYWORDS: Constructed wetlands; industrial wastewater; media; recirculation; removal.

Download English Version:

<https://daneshyari.com/en/article/8095173>

Download Persian Version:

<https://daneshyari.com/article/8095173>

[Daneshyari.com](https://daneshyari.com)