


Accepted Manuscript

Durability performance of concrete incorporating coarse aggregates from marble industry waste

António André, Jorge de Brito, Alexandra Rosa, Diogo Pedro



PII: S0959-6526(13)00640-9

DOI: [10.1016/j.jclepro.2013.09.037](https://doi.org/10.1016/j.jclepro.2013.09.037)

Reference: JCLP 3687

To appear in: *Journal of Cleaner Production*

Received Date: 18 March 2013

Revised Date: 21 August 2013

Accepted Date: 21 September 2013

Please cite this article as: André A, de Brito J, Rosa A, Pedro D, Durability performance of concrete incorporating coarse aggregates from marble industry waste, *Journal of Cleaner Production* (2013), doi: 10.1016/j.jclepro.2013.09.037.

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

**DURABILITY PERFORMANCE OF CONCRETE INCORPORATING
COARSE AGGREGATES FROM MARBLE INDUSTRY WASTE**

António André¹; Jorge de Brito¹; Alexandra Rosa¹; Diogo Pedro¹

¹ Department of Civil Engineering, Architecture, and Geo-resources, Instituto Superior Técnico, Technical University of Lisbon, Av. Rovisco Pais, 1049-001, Lisbon, Portugal

Corresponding author:

Jorge de Brito,

Department of Civil Engineering, Architecture, and Geo-resources, Instituto Superior Técnico, Technical University of Lisbon, Av. Rovisco Pais, 1049-001, Lisbon, Portugal.

Tel.: +351 218443659, Fax: +351 218443071, E-mail: jbrito@civil.ist.utl.pt

ABSTRACT

The quarrying of marble, a well-known ornamental stone, has a substantial positive impact on Portugal's economy, but it also generates large environmental impacts. The amount of waste produced during quarrying can be as much as 80% of all stone/soil extracted. That waste is then dumped near the quarry, where it accumulates indiscriminately because a viable alternative for its disposal has not yet been found. In this context, solutions must be found that can transform this waste into a by-product and restore some of its economic value. The main goal of this study was to evaluate the influence of the replacement of primary aggregates (PA) with marble aggregates. No additions or admixtures were used, as those could change the fresh or hardened properties of the resulting concrete and disguise the influence of the replacement under study. This evaluation required the production of three

Download English Version:

<https://daneshyari.com/en/article/8106986>

Download Persian Version:

<https://daneshyari.com/article/8106986>

[Daneshyari.com](https://daneshyari.com)