

Accepted Manuscript

Numerical study of water displacement from the elbow of an inclined oil pipeline

M. Magnini, A. Ullmann, N. Brauner, J.R. Thome

PII: S0920-4105(18)30253-5

DOI: [10.1016/j.petrol.2018.03.067](https://doi.org/10.1016/j.petrol.2018.03.067)

Reference: PETROL 4808

To appear in: *Journal of Petroleum Science and Engineering*


Received Date: 7 December 2017

Revised Date: 7 March 2018

Accepted Date: 15 March 2018

Please cite this article as: Magnini, M., Ullmann, A., Brauner, N., Thome, J.R., Numerical study of water displacement from the elbow of an inclined oil pipeline, *Journal of Petroleum Science and Engineering* (2018), doi: 10.1016/j.petrol.2018.03.067.

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



1 Numerical study of water displacement from the elbow
2 of an inclined oil pipeline

3 M. Magnini^{1*}, A. Ullmann^{2*}, N. Brauner^{2*}, J. R. Thome^{3*}

4 ¹ *Department of Chemical Engineering, Imperial College London, London SW7 2AZ,*
5 *United Kingdom*

6 ² *School of Mechanical Engineering, Faculty of Engineering, Tel Aviv University, 69978*
7 *Tel Aviv, Israel*

8 ³ *Laboratory of Heat and Mass Transfer (LTCM), Ecole Polytechnique Fédérale de*
9 *Lausanne (EPFL), EPFL-STI-IGM-LTCM, Station 9, CH-1015 Lausanne, Switzerland*

10 **Abstract**

When oil and water are simultaneously transported along a hilly-terrain pipeline, water may accumulate at low level sections during production shut-down. Since the contact of water with the internal wall of a steel pipe yields significant corrosion, it is desirable for the water accumulated to be flushed out by the flowing oil. As such, the underlying two-phase flow dynamics and its influential parameters, as well as the minimal flow rate of the continuous phase required for the displacement of the accumulated water, are of primary industrial interest. This work presents a numerical investigation of the conditions governing and promoting water displacement at the elbow between a horizontal and an upward inclined pipeline, considering diesel oil as the carrier phase, and an inside pipe diameter of 27 mm. The numerical framework adopted is the opensource CFD package OpenFOAM release 2.3.1, and two-phase flow transient simulations are run by employing the built-in Volume Of Fluid (VOF) algorithm. Due to the complex three-dimensional nature

*Corresponding author. E-mail: m.magnini@imperial.ac.uk
Preprint submitted to Journal of Petroleum Science and Engineering

Download English Version:

<https://daneshyari.com/en/article/8125056>

Download Persian Version:

<https://daneshyari.com/article/8125056>

[Daneshyari.com](https://daneshyari.com)