ARTICLE IN PRESS

JFDA528 proof **■** 18 August 2017 **■** 1/6

JOURNAL OF FOOD AND DRUG ANALYSIS XXX (2017) 1-6

Available online at www.sciencedirect.com

ScienceDirect

Original Article

Effects of electrode gap and electric current on chlorine generation of electrolyzed deep ocean water

Guoo-Shyng Wang Hsu^a, Shun-Yao Hsu^{b,*}

^a Department of Nutritional Science, Fu Jen Catholic University, Hsinchuang, New Taipei City, Taiwan ^b Graduate Institute of Food Science and Technology, National Taiwan University, Taipei, Taiwan

ARTICLE INFO

Article history: Received 1 March 2017 Received in revised form 15 July 2017 Accepted 21 July 2017 Available online xxx Keywords: Chlorine

Deep ocean water Electric efficiency Electrolyzed seawater Optimization

ABSTRACT

Electrolyzed water is a sustainable disinfectant, which can comply with food safety regulations and is environmental friendly. A two-factor central composite design was adopted for studying the effects of electrode gap and electric current on chlorine generation efficiency of electrolyzed deep ocean water. Deep ocean water was electrolyzed in a glass electrolyzing cell equipped with platinum-plated titanium anode and cathode in a constant-current operation mode. Results showed that current density, chlorine concentration, and electrolyte temperature increased with electric current, while electric efficiency decreased with electric current and electrode gap. An electrode gap of less than 11.7 mm, and a low electric current appeared to be a more energy efficient design and operation condition for the electrolysis system.

Copyright © 2017, Food and Drug Administration, Taiwan. Published by Elsevier Taiwan LLC. This is an open access article under the CC BY-NC-ND license (http:// creativecommons.org/licenses/by-nc-nd/4.0/).

1. Introduction

Electrolyzed water is environmental friendly, has significant disinfection effects and can comply with food safety regulations [1]. Since most surface area of our earth is covered by seawater, it is reasonable to make sustainable applications of this resource. Electrolyzed seawater, owing to its significant disinfection effects, has been used in many anti-fouling systems [2,3], aquaculture and seafood processing. For example, Kasai et al. [4,5] studied disinfectant effects of electrolyzed seawater on viable bacteria in hatchery seawater using a batch and a continuous electrolytic system. They reported a 2-4 log reduction of viable bacteria after treatment with electrolyzed seawater containing 0.5-1.0 mg/L chlorine for 1 min. Watanabe and Yoshimizu [6] disinfected various utensils and equipments for aquaculture and reported a >3 log reduction of viable bacteria after being treated with electrolyzed seawater containing 0.5-1.5 mg/L chlorine for 30-120 min. Kasai and Yoshimizu [7] studied disinfection of seawater from fishing port by an electrolytic apparatus and found its useful applications to sanitation of fish holding tanks, port deck and fishing equipment. Kimura et al. [8] reared sea urchins for 2 days using electrolyzed seawater

* Corresponding author. Fax: +886 2 2362 0849.

Please cite this article in press as: Hsu G-SW, Hsu S-Y, Effects of electrode gap and electric current on chlorine generation of electrolyzed deep ocean water, Journal of Food and Drug Analysis (2017), http://dx.doi.org/10.1016/j.jfda.2017.07.011



E-mail address: gifsthsu@ntu.edu.tw (S.-Y. Hsu).

http://dx.doi.org/10.1016/j.jfda.2017.07.011

^{1021-9498/}Copyright © 2017, Food and Drug Administration, Taiwan. Published by Elsevier Taiwan LLC. This is an open access article under the CC BY-NC-ND license (http://creativecommons.org/licenses/by-nc-nd/4.0/)

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

47

48

49

50

51

52

53

54

55

56

57

58

59

60

61

62

63

64

65

JOURNAL OF FOOD AND DRUG ANALYSIS XXX (2017) $\rm I-\!6$

containing 0.76 mg/L chlorine and found that 90% of bacteria in sea-urchins' viscera were eliminated. Kasai et al. [9] used electrolyzed seawater, which contained 0.2 mg/L chlorine to depurate contaminated oysters and found that *Escherichia* coli in the oysters was reduced to below detection limits.

Although many applications of electrolyzed seawater had been reported in aquaculture and seafood processing, few applications were reported in agriculture or food processing industry probably owing to its sanitary concerns. Plankton and bacteria are abundant in seawater and certain coastal seawater had been highly polluted [10,11]. By contrast, deep ocean water (DOW) is the cold, salty seawater found deep below the surface of earth's oceans. DOW makes up about 90% of the ocean volume. DOW has low temperature, typically from 0 °C to 3 °C, and a salinity of about 35 psu [12]. Although surface seawater can be contaminated by pollution or civilization, the high-pressure and low-temperature deep ocean water has remained unpolluted for the past thousand years.

In order to develop electrolyzed seawater for food and agricultural applications, especially for postharvest cleaning and disinfection of ready-to-eat fresh produce, surface seawater, DOW and DOW concentration products were electrolyzed, and their properties as well as storage stability were investigated in our previous studies [13,14]. Another study showed that optimal choice for electrode gap and cell potential depends on target chlorine level of the electrolyzed DOW and a small electrode gap is preferred [15]. A two-factor central composite design was adopted for an investigation on optimal electrolysis time and electric potential for electrolyzing DOW. Results showed that optimal choice of electrolysis time depends on chloride level in DOW and cell potential adopted. High electric potential resulted in fast chlorine generation, but reduced electric efficiency owing to temperature rise at the same time [16]. Since constant electric-current mode of operation has never been done before, a two-factor central composite design is adopted for further investigating optimal electrode gap and electric current for electrolyzing deep ocean water in this study.

2. Methods

2.1. Seawater samples

The Taiwan Yes Deep Ocean Water Co., Ltd. (Hualien County, Taiwan) provided DOW samples used in this study. DOW was drawn at 662 m below the Pacific Ocean at -5.0 km off the coastline of the Hualien County in eastern Taiwan. Table 1 shows a comparison of major elements, some pollution indicators and physical/chemical properties of the DOW with those of surface seawater samples collected at the nearby areas. Despite containing similar major elements, DOW appeared to be colder and purer than surface seawater, which contained more nitrite as well as chlorophyll and were more alkalinous in its pH values.

2.2. Electrolysis

DOW samples, 1600 mL each, were electrolyzed for 2 h in a 2.0 L glass-beaker electrolyzing cell equipped with a pair of

50 mm long imes 25 mm wide anode and cathode. The Anode and Cathode (Model SUR-303, Surchem C&S International Corp., Taipei City, Taiwan), which were titanium mesh electrode plated with 3.75 μ m of platinum, were powered by a Rectifier (Model MC48-4D, Surchem C&S International Corp.). The electrodes were immersed in seawater at 60 mm beneath the liquid surface. A constant current mode of operation was adopted in this study. Electrode gap and electric current were maintained at designated levels during electrolysis (Table 2). The levels were chosen based on preliminary tests. Additional stirring was done with a 16 \times 30 mm (diameter \times length) Teflon spindle-shape magnetic stir bar powered by a Stirrer (Model PC-101, Corning Inc., Acton, MA, USA) at speed setting 1.2, which was approximately 200 rpm. Electrolysis parameters and electrolyte properties were monitored during the electrolysis process.

2.3. Analytical measurements

A total chlorine test kit (Model 16900; Hach Co., Loveland, CO, USA; Method 8209, which is based on iodometric method.) was used to measure total residual chlorine in the electrolyzed seawaters. The assay was verified periodically using a 100 \pm 0.05 ppm chlorine standard solution (Orion Research Inc., Beverly, MA, USA). All measurements were conducted at 29 \pm 1 °C.

2.4. Electrolysis efficiency

Current density was calculated by dividing the electric current by the effective surface area of anode. Electric efficiency, which represents energy efficiency of the system, was calculated by dividing the total chlorine produced by the electric energy consumed. Current efficiency was calculated from the percentage ratio of the total chlorine produced to the theoretical chlorine production based on the Faraday's laws of electrolysis [17].

2.5. Statistical design and analysis

A two-factor central composite design [18] was adopted for studying the effects of electrode gap and electric current on chlorine generation efficiency of electrolyzed DOW. The test ranges of electrode gap and electric current were 6.7–20.1 mm and 2.5–5.5 A, respectively (Table 2). Four center-points were replicated for the estimation of random errors. Experimental data were analyzed by the response surface regression test of the Statistical Analysis Systems (SAS 9.4, SAS Institute, Cary, NC, USA).

3. Results and discussion

Electrolyzed seawater, because of its significant disinfection effects and availability, has been used in many anti-fouling, aquaculture and seafood processing systems. However, reports on design of electrolysis systems were mostly patented and detailed information on their mechanism as well as effects on electrolysis efficiencies was very limited. Therefore, the objectives of this study are to collect information on

Please cite this article in press as: Hsu G-SW, Hsu S-Y, Effects of electrode gap and electric current on chlorine generation of electrolyzed deep ocean water, Journal of Food and Drug Analysis (2017), http://dx.doi.org/10.1016/j.jfda.2017.07.011

Download English Version:

https://daneshyari.com/en/article/8520842

Download Persian Version:

https://daneshyari.com/article/8520842

Daneshyari.com