

## Original article

# Toward connectionist model for predicting bubble point pressure of crude oils: Application of artificial intelligence



Mohammad Ali Ahmadi <sup>a,\*</sup>, Maysam Pournik <sup>b</sup>, Seyed Reza Shadizadeh <sup>c</sup>

<sup>a</sup> Department of Petroleum Engineering, Ahwaz Faculty of Petroleum Engineering, Petroleum University of Technology, Ahwaz, Iran

<sup>b</sup> Department of Petroleum Engineering, Mewbourne School of Petroleum & Geological Engineering, University of Oklahoma, OK, United States

<sup>c</sup> Department of Petroleum Engineering, Abadan Faculty of Petroleum Engineering, Petroleum University of Technology, Abadan, Iran

## ARTICLE INFO

## Article history:

Received 11 June 2015

Received in revised form

10 August 2015

Accepted 31 August 2015

## Keywords:

Bubble point pressure

Swarm intelligence

Crude oil

Artificial intelligence

Reservoir fluid

## ABSTRACT

Knowledge about reservoir fluid properties such as bubble point pressure ( $P_b$ ) plays a vital role in improving reliability of oil reservoir simulation. In this work, hybrid of swarm intelligence and artificial neural network (ANN) as a robust and effective method was executed to determine the  $P_b$  of crude oil samples. In addition, the exactly precise  $P_b$  data samples reported in the literatures were employed to create and validate the PSO-ANN model. To prove and depict the reliability of the smart model developed in this study for estimating  $P_b$  of crude oils, the conventional approaches were applied on the same data set. Based on the results generated by PSO-ANN model and other conventional methods and equation of states (EOS), the PSO-ANN model is a reliable and accurate approach for estimating  $P_b$  of crude oils. This is certified by high value of correlation coefficient ( $R^2$ ) and insignificant value of average absolute relative deviation (AARD%) which are obtained from PSO-ANN outputs. Outcomes of this study could help reservoir engineers to have better understanding of reservoir fluid behavior in absence of reliable and experimental data samples.

Copyright © 2015, Southwest Petroleum University. Production and hosting by Elsevier B.V. on behalf of KeAi Communications Co., Ltd. This is an open access article under the CC BY-NC-ND license (<http://creativecommons.org/licenses/by-nc-nd/4.0/>).

## 1. Introduction

Generally, simulating numerically the hydrocarbon reservoirs, designing efficiently surface facilities, calculating precisely the inflow performance, estimating suitably reserves, analyzing logically the well testing generated data and gaining usefully from the material balance are strong functions of fluid PVT properties, specially the bubble point pressure ( $P_b$ ) which plays the leading role in all reservoirs' relevant calculations and developing plans [1–12].

Bubble point pressure in term is defined as the maximum pressure in which the first gas bubbles start forming and evolving [13].

In spite of reliable results generated normally with some experimental procedures about  $P_b$ , their time-consuming and expensive steps [14] besides their noticeable dependency towards the quality and quantity of gathered samples particularly when the pressure of the reservoir vicinity of the wellbore has fallen below the  $P_b$  have always been addressed as main concerns [15–18]. Having lack of ability to predict the target reservoir fluid properties under all the probable thermo dynamical conditions and requiring widespread and detailed knowledge about all compositions forming the oil sample which is a difficult determination in terms of money and time have all in all caused not also to consider Equation of States (EOS) as suitable  $P_b$  predicting methods whose accuracies are highly dependent to types of fluids, chosen equations, etc. [19–25].

Therefore, numerous numbers of researches including a variety of EOSs, a diversity of empirical correlations and cutting-edge artificial intelligence based methods have been proposed, derived and developed to overcome the referred hurdle and propose an appropriate solution to predict the  $P_b$ , even though

\* Corresponding author. Department of Petroleum Engineering, Ahwaz Faculty of Petroleum Engineering, Petroleum University of Technology, P.O. BOX: 63431, Ahwaz, Iran. Tel.: +98 912 6364936.

E-mail address: [ahmadi6776@yahoo.com](mailto:ahmadi6776@yahoo.com) (M.A. Ahmadi).

Peer review under responsibility of Southwest Petroleum University.



using some local data to suggest these models is a disadvantage which leads them not to become as much as useful and popular methods to be referenced in all geological areas of the world [13]. In more details, gas solubility, gas gravity, oil gravity and reservoir temperature were firstly taken by Standing to propose a model to predict  $P_b$  [26]. Based on oil samples without any non-hydrocarbon impurities and the Henry's law, Lasater performed a model to predict the supposed bubble point pressure [27]. Also, a graphical model which assumes corrections for the presence of gaseous impurities such as  $H_2$ ,  $N_2$  and  $H_2S$  gained from North Sea data was built by Glasoto predict series of parameters including  $P_b$ ,  $B_o$ , total oil formation volume factor ( $B_t$ ) and  $\mu_o$  [28]. After running very detailed numerical analysis on a very large and extensive data center, Velarde et al. tuned the already aroused correlations up by introducing a new coefficient [29]. Moreover, Gharbi and Elsharkawy initially implemented an Artificial Neural Network (ANN) to predict PVT properties consist of  $P_b$  for crude oil samples gathered from Middle East [30]. Once again Gharbi et al. designed another multilayer perceptron ANN to predict  $P_b$  through forming a massive data center gathered from all parts of the world [31]. Next, El-Sebakhy et al. generated a formula to predict the  $P_b$  and  $B_o$  by using support vector regressions and gaining from 3 different PVT databases [32]. Regardless of triumphs represented by applying ANN models to predict PVT properties, its inherent limitations and constrains have caused researcher to look for more analytical, precise and robust methods capable of defeating obstacles resulted from vagueness, complexities, ambiguities and nonlinear behavior natures of reservoirs parameters [33,34]. All in all, made efforts gave rise to put forward applications of up-to-the-minute soft computing schemes such as using Adaptive Neuro-Fuzzy Inference System (ANFIS) normally in predictions of the reservoir characterizations and operations [35] or conducting approach of Support Vector Machine (SVM) to predict the  $P_b$  factor, the study that took a set of compositional, handy PVT properties and reservoir thermo dynamical parameter as input [13].

Furthermore, the aim of this research is summarized to introduce and develop a user friend, effective and sharp model to estimate bubble point pressure ( $P_b$ ) of crude oil samples. To gain this end, hybrid of swarm intelligence and neural network as robust type of artificial intelligent methods was executed to tackle the aforementioned target of this study. Massive  $P_b$  data banks extracted from previous works [36–55] were employed to test and validate the PSO-ANN model. To certify the efficiency and integrity of the PSO-ANN model, conventional methods and EOSs were employed to predict the  $P_b$  of crude oils. The results gained from both PSO-ANN and EOS models are demonstrated in details in further sections.

## 2. Data gathering

To start carrying the introduced correlation out, it is necessary to from a database. Farasat et al. [13] published full set data center which includes 123 records in four main divisions to predict the predict  $P_b$  [13]. Those are Temperature ( $^{\circ}F$ ), bubble point pressure ( $P_b$ ) and reservoir fluid composition such as nitrogen, methane, ethane, propane, etc. mole fractions. The overview of the published data summarized through Table 1.

## 3. Methodology

### 3.1. Artificial neural network (ANN)

ANN, a bio-inspired approach which their initial pattern has been recognized from studying the everyday procedures of

**Table 1**

Statistical parameters of the implemented bubble point pressure data set [13].

Variables	Min	Max	Average
Bubble point pressure, psia	313	6880	2283.2
Temperature, $^{\circ}F$	128	324	177.3
Hydrogen sulfide, mol fraction	0	3.68	0.14
Carbon dioxide, mol fraction	0	9.11	1.09
Nitrogen, mol fraction	0	1.67	0.36
Methane, mol fraction	5.63	74.18	33.10
Ethane, mol fraction	0.84	12.45	7.35
Propane, mol fraction	0.43	11.87	6.33
Butanes, mol fraction	0.95	8.40	4.58
Pentanes, mol fraction	0.40	6.65	3.27
Hexanes, mol fraction	0	6.65	3.20
Heptanes-plus, mol fraction	10.72	83.20	40.63
Molecular weight $C_{7+}$	134	324	230.9
Specific gravity $C_{7+}$	0.743	0.942	0.861

human brain, is succinctly capable of correlating numerically and inversely the relationships between inputs and outputs of each supposed system by thanks to their distinctive mathematical structures. The gathered laboratorial data are technically implemented to train the network then; the prepared network is gained to estimate the imprecise and blurred data [56–71]. The depicted scheme is conductible through relying on synchronous processing units, known as neurons and nodes, located in layers. The input layer, a certain number of hidden layers and an output layer are the basic components of each ANN which the number of their neurons are specified by the available data, designers and target of the discussed problem, respectively. Indisputably, the back-propagation feed forward network and specifically the multilayer perceptron (MLP) networks, those evaluate through considering the classical techniques in relation to their much reduced development time and their potential to make usage of related info, are the most promising and popular kinds of ANN in petroleum engineering [56–66,69–76].

Before tackling by details to the main issue of this study which is carrying an up-to-the-minute optimizing method out to set precisely the ANN related variables. The referred theme has been followed by dividing the database into two main parts apparently named training and testing sets. Regarding this division is due to determine the most appropriate network structure by applying the larger group, training ones, while the testing set which has not earlier been faced to the network in the training step is piloted to examine the reliability of the proposed network in the case of correlating the bubble point pressure. Running the optimization of interconnected weights and node biases is continued up till the performance of the proposed ANN is based on some statistical criteria like Mean Squared Error (MSE) permissible and it is when the values of outputs at the neurons of output layer are very nearly close to the corresponding experimental data [56–60]. The MSE is expressed as follow

$$MSE^{Approach} = \frac{1}{2} \sum_{k=1}^G \sum_{j=1}^m [Y_j(k) - T_j(k)]^2 \quad (1)$$

In which  $m$  stands for the number of output nodes,  $G$  denotes the number of training samples,  $Y_j(k)$  stands for the expected target, and  $T_j(k)$  denotes the real target. When the MSE closes gradually to the zero, the error of our developed network model starts declining [56–66,69–71] (see Fig. 1).

Download English Version:

<https://daneshyari.com/en/article/852865>

Download Persian Version:

<https://daneshyari.com/article/852865>

[Daneshyari.com](https://daneshyari.com)