# Accepted Manuscript




A comparison of various MRI feature types for characterizing whole brain anatomical differences using linear pattern recognition methods

Gemma C. Monté-Rubio, Carles Falcón, Edith Pomarol-Clotet, John Ashburner

PII: S1053-8119(18)30491-9

DOI: 10.1016/j.neuroimage.2018.05.065

Reference: YNIMG 14990

To appear in: *NeuroImage*

Received Date: 17 October 2017

Revised Date: 24 April 2018

Accepted Date: 27 May 2018

Please cite this article as: Monté-Rubio, G.C., Falcón, C., Pomarol-Clotet, E., Ashburner, J., A comparison of various MRI feature types for characterizing whole brain anatomical differences using linear pattern recognition methods, *NeuroImage* (2018), doi: 10.1016/j.neuroimage.2018.05.065.

# A comparison of various MRI feature types for characterizing whole brain anatomical differences using linear pattern recognition methods

Gemma C. Monté-Rubio[1, 2], Carles Falcón[3, 4], Edith Pomarol-Clotet[1], John Ashburner[5*]

1. FIDMAG Germanes Hospitalàries Research Foundation, Avda. Jordà 8, 08035 -Barcelona, Spain. E-mail EPC: epomarol-clotet@fidmag.com
2. Fundació ACE. Institut Català de Neurociències Aplicades. Marqués de Sentmenat 57, 08029 - Barcelona, Spain. E-mail GCMR: gmonte@fundacioace.com
3. Barcelonaβeta Brain Research Center, Pasqual Maragall Foundation. Barcelona, Carrer de Wellington 30, 08005 – Barcelona, Spain. E-mail CF:cfalcon@barcelonabeta.org
4. CIBER en Bioingenieria, Biomateriales y Nanomedicina (CIBER-BBN), Spain.
5. Wellcome Centre for Human Neuroimaging, UCL Institute of Neurology, 12 Queen Square, London- WC1N 3BG, UK. E-mail JA (*corresponding author): j.ashburner@ucl.ac.uk

Key words: pattern recognition, Gaussian process, diffeomorphism, model selection.