


## Accepted Manuscript

Topographic filtering simulation model for sediment source apportionment

Se Jong Cho, Peter Wilcock, Benjamin Hobbs



PII: S0169-555X(18)30062-X  
DOI: doi:[10.1016/j.geomorph.2018.02.014](https://doi.org/10.1016/j.geomorph.2018.02.014)  
Reference: GEOMOR 6326  
To appear in: *Geomorphology*  
Received date: 7 October 2017  
Revised date: 6 February 2018  
Accepted date: 6 February 2018

Please cite this article as: Se Jong Cho, Peter Wilcock, Benjamin Hobbs , Topographic filtering simulation model for sediment source apportionment. The address for the corresponding author was captured as affiliation for all authors. Please check if appropriate. Geomorph(2017), doi:[10.1016/j.geomorph.2018.02.014](https://doi.org/10.1016/j.geomorph.2018.02.014)

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

## Topographic Filtering Simulation Model for Sediment Source Apportionment

Se Jong Cho<sup>1</sup>, Peter Wilcock, and Benjamin Hobbs

*Department of Geography and Environmental Engineering, Johns Hopkins University,  
Baltimore, Maryland, USA*

### Abstract

We propose a Topographic Filtering simulation model (Topofilter) that can be used to identify those locations that are likely to contribute most of the sediment load delivered from a watershed. The reduced complexity model links spatially distributed estimates of annual soil erosion, high-resolution topography, and observed sediment loading to determine the distribution of sediment delivery ratio across a watershed. The model uses two simple two-parameter topographic transfer functions based on the distance and change in elevation from upland sources to the nearest stream channel and then down the stream network. The approach does not attempt to find a single best-calibrated solution of sediment delivery, but uses a model conditioning approach to develop a large number of possible solutions. For each model run, locations that contribute to 90% of the sediment loading are identified and those locations that appear in this set in most of the 10,000 model runs are identified as the sources that are most likely to contribute to most of the sediment delivered to the watershed outlet. Because the underlying model is quite simple and strongly anchored by reliable information on soil erosion, topography, and sediment load, we believe that the ensemble of simulation outputs provides a useful basis for identifying the dominant sediment sources in the watershed.

---

<sup>1</sup> Corresponding author: Se J. Cho (chos@umn.edu)

Download English Version:

<https://daneshyari.com/en/article/8908050>

Download Persian Version:

<https://daneshyari.com/article/8908050>

[Daneshyari.com](https://daneshyari.com)