

## Accepted Manuscript

Energy and water benchmarks for aquatic centres in Victoria,  
Australia

Jean Jonathan Duverge , Priyadarsini Rajagopalan , Robert Fuller ,  
Jin Woo

PII: S0378-7788(17)33341-8  
DOI: <https://doi.org/10.1016/j.enbuild.2018.07.043>  
Reference: ENB 8714



To appear in: *Energy & Buildings*

Received date: 7 October 2017  
Revised date: 19 July 2018  
Accepted date: 21 July 2018

Please cite this article as: Jean Jonathan Duverge , Priyadarsini Rajagopalan , Robert Fuller ,  
Jin Woo , Energy and water benchmarks for aquatic centres in Victoria, Australia, *Energy & Build-  
ings* (2018), doi: <https://doi.org/10.1016/j.enbuild.2018.07.043>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

## Highlights:

- Establish the energy and water benchmark of aquatic centres from data collected from 22 aquatic centres using statistical analysis.
- Conditioned usable floor area to be used as a variable for benchmarking the energy use of aquatic centres.
- The proposed energy benchmark for aquatic centres ranges between 648 kWh/m<sup>2</sup> to 2283 kWh/m<sup>2</sup>.
- Number of visitors to be used as a variable for benchmarking the water use of aquatic centres.
- The proposed water benchmark for aquatic centres ranges between 11 L/Visitor to 110 L/Visitor.

Download English Version:

<https://daneshyari.com/en/article/8941544>

Download Persian Version:

<https://daneshyari.com/article/8941544>

[Daneshyari.com](https://daneshyari.com)